VG2236wm-LED

Appendix 5
Revised 05/13/13

22" (21.5" VIEWABLE) WIDESCREEN LED MONITOR WITH HEIGHT ADJUST, SPEAKERS AND ENERGY STAR® 5.0

LCD	Type	22" (21.5" viewable) Wide Color TFT Active Matrix LCD
	Display Area	18.8" horizontal x 10.6" vertical; 21.5" diagonal
	Optimum Resolution	1920x1080
	Contrast Ratio	1000:1 (typ); 20,000,000:1 (dynamic)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 30,000 hrs. (typ)
	Brightness	250 cd/m^2 (typ)
	Panel Surface	Anti-glare, hard-coating (3H)
VIDEO INPUT	Analog	RGB analog (75 ohms, 0.7/1.0 Vp-p)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F_H: 24~83kHz, F_V: 50~75Hz
	Sync	H/V separated (TTL), composite sync-on-green
COMPATIBILITY	PC	VGA up to 1920x1080 non-interlaced
	Mac®*	Power Mac™ up to 1920x1080
CONNECTOR	Analog	15-pin mini D-sub (VGA)
	Digital	DVI-D
	Audio	3.5 mm audio in
	Power	3-pin plug (CEE22)
AUDIO	Speakers	2x2W
POWER	Voltage	AC 100–240V (universal), 50/60Hz
	Consumption	22W (typ)
CONTROLS	Basic	Power, 1, down, up, 2
	OSD	Auto Image Adjust, Contrast/Brightness, Input Select (D-SUB, DVI), Audio adjust (Volume mute), Color Adjust (sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B]), Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, Eco-mode), Setup Menu (Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off), Memory Recall
ERGONOMICS	Tilt	Down 5°, Up 20°
	Swivel	360°
	Height Adjust	0-135mm
	Pivot	0-90°
OPERATING CONDITIONS	Temperature	32–104° F (0–40° C)
	Humidity	20–90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	20.52" x 16.48" x 9.42" (521.21mm x 418.63mm x 239.2mm)
	Physical without stand	20.52" x 12.66" x 2.02" (521.21mm x 321.71mm x 51.5mm)
	Packaging	23.46" x 19.01" x 6.81" (596mm x 483mm x 173mm)
WEIGHT	Net with stand	9.7 lb. (4.4 kg)
	Net without stand	7.5 lb. (3.4 kg)
	Gross	15.4 lb. (7.0 kg)
WALL MOUNT		VESA® 100mm x 100mm
REGULATIONS		UL, CUL, FCC-B (ICES), CB, CE, CES-003B, ISO13406-2, TUV/GS, ERGO, TUV-S, NOM, GOST-R, HYGIENIC (20 copies), CCC, BSMI, PSB, C-TICK, MIC(KCC), SASO, WEEE, RoHS, SASO, Ukraine, TCO, EPEAT Gold
POWER MANAGEMENT		ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, power cable, DVI cable, audio cable, Quick Start Guide ViewSonic Wizard CD (User Guide and drivers)
WARRANTY		Three-year limited warranty on parts, labor and backlight.

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows is a trademark of Microsoft Corporation registered in the U.S. and other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved. [15137-02B-11/10] VG2236wm-LED

ViewSonic® See the difference®

For more product information, visit us on the web at ViewSonic.com