



1 REFLECTED CEILING PLAN
 A-141 SCALE: 1"=20'

SYMBOL LEGEND

- ✕ VENT THRU ROOF TO BE DEMOLISHED. (SEE DEMOLITION NOTE 7 AND DEMOLITION SHEETS.)
- ELEC. / PLUMB. / MECH. PIPE ROOF PENETRATION. DIAMETER VARIES. (CONFIRM DIAMETER IN FIELD AND COORDINATE WITH DETAILS 1/A502 AND 10/A502)
- + ROOF DRAIN RETROFIT / INSERT (SEE DETAIL 3/A502)
- PITCH POCKET (SEE DETAIL 2/A502)
- EXISTING ELECTRICAL PANEL (SEE ALSO ELECTRICAL SHEETS)
- ⊠ ROOFTOP EQUIPMENT
- 07 KEYNOTE
- ⊠2 DRAWING REFERENCE FOR DETAIL / SECTION CUT
- NEW ROOF SLOPE DIRECTION (1/8" per foot TAPERED INSULATION)
- NEW ROOF SLOPE DIRECTION (1/4" per foot TAPERED INSULATION)
- CONDENSATE LINE
- GAS LINE
- WATER LINE
- ~ EXPANSION JOINT
- ▨ PLASTER OR GYPBOARD
- ▨ EXISTING ACOUSTICAL CEILING TILE
- ▨ NEW ACOUSTICAL CEILING TILE
- EXISTING LANDSCAPING

REFLECTED CEILING PLAN KEY NOTES

1. CONTRACTOR TO LOCATE NEW THRU-ROOF PENETRATION(S) TO ACCOMMODATE NEW REROUTED CONDENSATE LINE PLUMBING DESIGN SO THAT THE PIPE DROPS VERTICALLY INTO THE CORNER OF MOP SINK AREA AS INDICATED. NEW PIPE SHALL TIE INTO THE EXISTING SINK DRAIN BELOW THE FIXTURE. (REFER TO PLUMBING AND MECHANICAL SHEETS) CONTRACTOR SHALL CUT THROUGH EXISTING CONSTRUCTION AN OPENING WITH MINIMUM DIMENSIONS NECESSARY FOR THE WORK. CONTRACTOR SHALL REPAIR ALL EXISTING CONSTRUCTION THAT IS DISTURBED BY DEMOLITION AND NEW CONSTRUCTION. ALL EXPOSED LENGTH OF PIPE WILL BE PAINTED COLOR CHOSEN BY ARCHITECT.
2. WHERE NEW CONDENSATE LINE ENTERS INTO A FINISHED SPACE, CONTRACTOR IS TO LOCATE NEW THRU ROOF PENETRATION(S) TO ACCOMMODATE REROUTED CONDENSATE LINE PLUMBING DESIGN SO THAT INTERIOR TRAP REMAINS ABOVE THE CEILING AS IT TIES INTO AN EXISTING, ACTIVE VENT STACK AND DRAIN ASSEMBLY. REFER TO PLUMBING AND MECHANICAL SHEETS. NOTE: ANY EXISTING CONSTRUCTION THAT REQUIRES TEMPORARY REMOVAL DURING THIS WORK SHALL BE REPAIRED AND RESTORED TO ITS ORIGINAL CONDITION BY THE CONTRACTOR AS AN INCLUDED COST WITHIN THE SCOPE OF THIS WORK. TEMPORARILY REMOVE CEILING TILES (AND SUSPENSION SYSTEMS IF REQUIRED) FOR ACCESS TO CONDENSATE TRAP LOCATIONS. REINSTALL CEILING SYSTEMS UPON COMPLETION OF PLUMBING WORK..
3. EXTEND NEW CONDENSATE LINES FROM RTU-7 AND RTU-10 THRU THE WALL ABOVE THE ROOF. CORE DRILL CONDENSATE LINE ACCESS PORTAL AND GROUT NEW GALVANIZED STEEL PIPE SLEEVE IN PLACE. COORDINATE REQUIRED SIZE OF NEW SLEEVE WITH CONDENSATE LINE (REFER TO MECHANICAL). UPON COMPLETION OF CONDENSATE LINE ROUTING THROUGH SLEEVE, GROUT VOIDS IN EXTERIOR END OF SLEEVE AROUND CONDUIT WEATHERTIGHT. TEMPORARILY REMOVE CEILING TILES (AND SUSPENSION SYSTEMS IF REQUIRED) FOR THE INSTALLATION AND REINSTALL. DRAIN WILL EMPTY DIRECTLY INTO FLOOR MOP SINK OF JANITOR SPACE AS SHOWN. CONTRACTOR SHALL FIELD VERIFY EXACT LOCATION OF SINK. REFER TO PLUMBING SHEET.
4. CONTRACTOR TO LOCATE NEW THRU-ROOF PENETRATION(S) TO ACCOMMODATE NEW ELECTRICAL SERVICE SO THAT THE PIPE DROPS VERTICALLY INTO THE SPACE TO TIE NEATLY INTO THE EXISTING PANEL INDICATED (REFER TO ELECTRICAL SHEETS). CONTRACTOR SHALL CUT THROUGH EXISTING CONSTRUCTION AN OPENING WITH MINIMUM DIMENSIONS NECESSARY FOR THE WORK. CONTRACTOR SHALL REPAIR ALL EXISTING CONSTRUCTION THAT IS DISTURBED BY DEMOLITION AND NEW CONSTRUCTION TO MATCH EXISTING ADJACENT CONSTRUCTION TO REMAIN. ALL EXPOSED LENGTH OF PIPE WILL BE PAINTED COLOR CHOSEN BY ARCHITECT. SEE ADDITIVE ALTERNATE #3.

GENERAL NOTE:

CONTRACTOR SHALL FIELD VERIFY LOCATION OF ALL INDICATED FIXTURES AND CONFIRM THEIR CONNECTIONS TO ACTIVE VENTS THRU THE ROOF. CONTRACTOR SHALL NOTIFY ARCHITECT UPON DISCOVERY OF ANY DISCREPANCY.

revisions	
no.	date

seal

john pruetts architects
 1869 madison ave.
 memphis, tn 38104
 (901) 721-9062
 pruettsarchitects@bellsouth.net
 www.pruettarchitects.com

ROOF REPLACEMENT
Peggy Edmiston Administration Building
 1075 Mullins Station Road, Memphis, TN 38134

BID DOCUMENT SET
 RFP # 14-011-24-A

sheet name
REFLECTED CEILING PLAN

date
11.18.2013

A-141