


1 FOUNDATION & FRAMING PLAN
 SCALE: 1/8" = 1'-0"



NOTES

DO NOT SCALE THESE DRAWINGS;
 RELATIVE DISTANCE BETWEEN FOOTINGS/COLUMNS ARE DEFINED ON THIS PLAN; ADDITIONAL INFORMATION ON LOCATING FOOTINGS TO AVOID (E)UTILITIES AND BUILDING FOOTINGS IS FOUND ON S3.0; ARCHITECT SHALL SPECIFY ABSOLUTE LOCATIONS (I.E. ORIGIN POINTS & ALIGNMENT)

SEE ARCHITECTURAL DRAWINGS FOR: DECK EXTENTS & COLUMN HEIGHTS & BEAM SLOPES, ETC; ROOF DECK SHALL BE: EPIC WP750 16/18; MAX SIMPLE SPAN = 32'-0"; MAX CANTILEVER = 16'-0"; 3-#12 SELF-TAPPING SCREWS ANCHORING EA 36" WIDE PANEL TO SUPPORT BEAMS; SIDELAP FASTENERS PER MANUFACTURER;
 SEE NOTES ON S3.0 AND S3.1 FOR ADDITIONAL INFO;


UTILITIES SURVEY SHOWN IN BACKGROUND FOR CONVENIENCE. ARCHITECT TO DETERMINE WHICH UTILITIES ARE ALLOWED TO BE CUT.
 SEE ACTUAL SURVEY DRAWINGS OR DIGITAL FILE BY "ETI" FOR THE SURVEY INFO.

UGU= underground unknown
 UGG= underground gas
 UGS = underground sewer
 UGE= underground electric
 UGW= underground water
 UG DRAINS= Storm Sewers(sometimes labeled 'sewers')

LEGEND

<p>TYPICAL FOUNDATION</p> <p>⊙ 10" PIPE COLUMN ON 24" DRILLED PIER</p>	<ul style="list-style-type: none"> • SEE 1/S3.1 FOR SUPERSTRUCTURE • SEE 1/S3.0 FOR FOUNDATION • DRILLED PIERS ARE TYPE A, UNLESS NOTED 'TYPE B'
<p>HSS9x5</p>	<p>BEAM @ ROOF LEVEL SUPPORTING 'EPIC' DECK; ALL HSS SECTIONS ARE 1/2" THICK, U.N.O; SEE 1/S3.1 FOR TYPICAL ELEVATION</p>
<p>HSS10x4</p>	<p>BEAM @ ROOF LEVEL SUPPORTING 'EPIC' DECK @ EXP. JOINT, EXP. JOINT SEE 4/S3.1 FOR TYPICAL EXP. JOINT DETAIL</p>

revisions	
no.	date
1	6-12-15



john pruet architects
 1869 madison ave.
 memphis, tn 38104
 (901) 721-9062

pruetarchitects@bellsouth.net
 www.pruetarchitects.com

Shelby County Department of Corrections

WALKWAY CANOPY

1045 Mullins Station Road, Memphis, TN 38134

BID SET

sheet name

EAST END STRUCTURAL PLAN

date

06/12/2015

S2.2