STATE OF TENNESSEE

SHELBY COUNTY

DIVISION OF PUBLIC WORKS PLAN FOR PROPOSED IMPROVEMENTS

CONGESTION MANAGEMENT PROGRAM

SIGNALIZATION OF VARIOUS LOCATIONS THROUGHOUT SHELBY COUNTY SIGNAL SYSTEM PROJECT SET #8

SCOPE OF WORK

THE SCOPE OF WORK INCLUDES INSTALLING CONDUIT WITH FIBER OPTIC INTERCONNECT CABLE ALONG JACKSON AVENUE/AUSTIN PEAY HIGHWAY FROM WALES ROAD TO YALE ROAD AND ALONG JAMES ROAD/STAGE ROAD ALSO INCLUDES THE INSTALLATION OF VIDEO DETECTION AND/OR EMERGENCY VEHICLE PREEMPTION EQUIPMENT AT SELECT INTERSECTIONS AND INSTALLATION OF RADAR DETECTION EQUIPMENT AT SELECT

- PROJECT LOCATIONS

LOCATIONS WITHIN THE PROJECT AREA.

- PROJECT INTERSECTION LOCATIONS

PROJECT RADAR DETECTION SYSTEM LOCATIONS

INDEX OF SHEETS

| SHEET NO. | DESCRIPTION | | | |
|-----------|--|--|--|--|
| 1 | COVER SHEET | | | |
| 2 | ESTIMATED QUANTITIES AND STANDARD DRAWINGS | | | |
| 3 | GENERAL NOTES AND SPECIAL NOTES | | | |
| 4 | SUMMARY OF WORK BY INTERSECTION | | | |
| 5 | COMMUNICATIONS CABLE SCHEMATIC AND LEGEND | | | |
| 6 | COMMUNICATIONS CHANNEL SCHEMATIC | | | |
| 7-17 | CABLE LAYOUT SHEETS | | | |
| 18-25 | INTERSECTION LAYOUT SHEETS | | | |
| 26-27 | RADAR DETECTION SYSTEM LAYOUT SHEETS | | | |
| 28-36 | SPLICING DIAGRAM SHEETS | | | |
| 37-47 | EXISTING UTILITIES SHEETS | | | |
| 48-50 | MISCELLANEOUS DETAILS | | | |


CONSULTANT DESIGN CONSTRUCTION

TDOT LOCAL PROGRAM MANAGER WHITNEY SULLIVAN SHELBY COUNTY PROJECT MANAGER _ ROBERT EVANS

CHECKED BY <u>MICHAEL AGNEW, P.E.</u> DESIGNED BY NEEL-SCHAFFER, INC.

DESIGNER BARRY ALEXANDER, P.E.

P.E. NO. 79LPLM-F3-291 PIN NO. 115241.14




VICINITY MAP NOT TO SCALE EQUATIONS: NONE EXCEPTIONS: NONE

TDOT P.I.N.:

115241.14 FEDERAL PROJECT NO.: CM - 7900(50)STATE PROJECT NO .: 79LPLM-F3-291

LOCALLY MANAGED PROJECT



PROPOSALS MAY BE REJECTED BY THE COUNTY ENGINEER IF ANY OF THE UNIT PRICES CONTAINED THEREIN ARE OBVIOUSLY UNBALANCED, EITHER EXCESSIVE OR BELOW THE REASONABLE COST ANALYSIS VALUE.

CONTRACTOR SHALL BE RESPONSIBLE FOR NOTIFYING ANY BOUNDARIES OF THE PROJECT PRIOR TO THE INITIATION OF ANY CONSTRUCTION ON THE PROJECT OR IN THE STREETS BORDERING THE PROJECT. THE CONTRACTOR SHALL ALSO ASSUME RESPONSIBILITY FOR ALL DAMAGE TO ANY UTILITY LINES, WHETHER SHOWN ON THE CONSTRUCTION PLANS OR NOT, DURING WORK ON THE PROJECT.

THIS PROJECT TO BE CONSTRUCTED UNDER THE STANDARD SPECIFICATIONS OF THE TENNESSEE DEPARTMENT OF TRANSPORTATION DATED MARCH 1, 2006 AND ADDITIONAL SPECIFICATIONS AND SPECIAL PROVISIONS CONTAINED IN THE PLANS AND IN THE PROPOSAL CONTRACT.

HON. MARK H. LUTTRELL, JR, MAYOR

| PPROVED: | MR. DARREN SANDERS, P.E. SHELBY COUNTY ENGINEER | DATE: | |
|----------|--|-------|--|
| PPROVED: | CITY OF MEMPHIS ENGINEER | DATE: | |
| PPROVED: | CITY OF MEMPHIS TRAFFIC ENGINEER | DATE: | |



| | | ESTIMATED ROADWAY QUANTITIES | | |
|----|-----------|--|------|----------|
| | ITEM NO. | DESCRIPTION | UNIT | QUANTITY |
| | 209-01.10 | EROSION AND SILTATION CONTROL | L.S. | 1 |
| 13 | 701-01.01 | CONCRETE SIDEWALK (4 ") | S.F. | 400 |
| 13 | 701-02.01 | CONCRETE CURB RAMP (RETROFIT) | S.F. | 300 |
| | 712-01 | TRAFFIC CONTROL | L.S. | 1 |
| | 712-04.01 | FLEXIBLE DRUMS (CHANNELIZING) | EACH | 100 |
| | 712-06 | SIGNS (CONSTRUCTION) | S.F. | 792 |
| | 712-08.03 | ARROW BOARD (TYPE C) | EACH | 4 |
| 1 | 714-25.09 | ELECTRICAL CONNECTION (FOR MLGW COST ONLY) | EACH | 2 |
| | 717-01 | MOBILIZATION | L.S. | 1 |
| 2 | 725-02.79 | FIBER SPLICE ENCLOSURE(WEATHER PROOF) | EACH | 15 |
| 19 | 725-03.09 | ETHERNET SWITCH (TYPE A) | EACH | 14 |
| 20 | 725-03.10 | ETHERNET SWITCH (TYPE B) | EACH | 1 |
| 15 | 725-03.60 | CABLE MARKER | EACH | 16 |
| 21 | 725-21.22 | TERMINAL SERVER (SERIAL DEVICE SERVER) | EACH | 2 |
| 4 | 725-21.88 | BLUETOOTH DETECTION SYSTEM | EACH | 2 |
| 3 | 725-21.91 | RADAR DETECTION SYSTEM | EACH | 7 |
| 3 | 725-21.96 | RDS COMM CABLE | L.F. | 400 |
| 14 | 725-21.97 | SOLAR POWER FOR RDS | EACH | 5 |
| 22 | 725-24.01 | CABINET (TYPE A) | EACH | 6 |
| 22 | 725-24.04 | CABINET (TYPE D) | | 1 |
| 23 | 725-24.11 | ITS COMMUNICATIONS HUB (INCLUDING PATCH PANEL) | | 1 |
| 16 | 730-01.02 | REMOVAL OF SIGNAL EQUIPMENT | EACH | 7 |
| | 730-02.17 | SIGNAL HEAD ASSEMBLY (150 A2H WITH BACKPLATE) | EACH | 2 |
| | 730-02.18 | SIGNAL HEAD ASSEMBLY (150 A2V) | EACH | 2 |
| | 730-03.21 | INSTALL PULL BOX (TYPE B) | EACH | 6 |
| 5 | 730-03.23 | INSTALL PULL BOX (FIBER OPTIC-TYPE A) | EACH | 49 |
| 6 | 730-03.24 | INSTALL PULL BOX (FIBER OPTIC-TYPE B) | EACH | 15 |
| | 730-03.31 | FIBER DISTRIBUTION BOX | EACH | 14 |
| 7 | 730-05.01 | ELECTRICAL SERVICE CONNECTION | EACH | 2 |
| | 730-08.02 | SIGNAL CABLE - 5 CONDUCTOR | L.F. | 230 |
| | 730-08.03 | SIGNAL CABLE - 7 CONDUCTOR | L.F. | 460 |
| 8 | 730-08.40 | INTERCONNECT CABLE - FIBER OPTIC (36-FIBER, SINGLE MODE) | L.F. | 58250 |
| 8 | 730-08.41 | INTERCONNECT CABLE - FIBER OPTIC (DROP CABLE, 6-FIBER, SINGLE MODE) | L.F. | 1120 |
| 8 | 730-08.42 | INTERCONNECT CABLE - FIBER OPTIC (DROP CABLE, 36-FIBER, SINGLE MODE) | L.F. | 200 |
| | 730-12.02 | CONDUIT 2" DIAMETER (PVC) | L.F. | 10820 |
| | 730-12.03 | CONDUIT 3" DIAMETER (PVC) | L.F. | 100 |
| 17 | 730-12.08 | CONDUIT 2" DIAMETER (RGS) | L.F. | 800 |
| 18 | 730-12.09 | CONDUIT 3" DIAMETER (RGS) | L.F. | 1510 |
| | 730-12.13 | CONDUIT 2" DIAMETER (JACK AND BORE) | L.F. | 15520 |
| | 730-12.42 | CURB MARKER (CURB MOUNTED CABLE MARKER) | EACH | 260 |
| 9 | 730-13.02 | VEHICLE DETECTOR (VIDEO) | EACH | 7 |
| 10 | 730-13.03 | VEHICLE DETECTOR (4 - CHANNEL, RACK MOUNT) | EACH | 19 |
| | | VEHICLE DETECTOR (OPTICALLY ACTIVATED PRIORITY | | |
| 11 | 730-13.06 | CONTROL) | EACH | 8 |
| | 730-14.01 | SHIELDED DETECTOR CABLE | L.F. | 160 |
| | 730-15.12 | MODIFY CABINET (BASE-MOUNT ENTRANCE) | EACH | 3 |
| | 730-15.15 | MODIFY CABINET (INSTALL DUPLEX GFI OUTLET) | EACH | 3 |
| | 730-15.32 | CABINET (EIGHT PHASE BASE MOUNTED) | EACH | 5 |
| 12 | 730-16.02 | EIGHT PHASE ACTUATED CONTROLLER | EACH | 6 |
| | 730-23.30 | PEDESTAL POLE (ALUMINUM, 20' LENGTH) | EACH | 7 |
| | 803-01 | SODDING (NEW SOD) | S.Y. | 800 |

FOOTNOTES:

- 1. ALLOWANCE TO COVER THE COST ASSOCIATED WITH POWER CONNECTION FOR THE TRAFFIC SIGNAL OR RDS UNIT FROM THE TRANSFORMER TO THE DEMARCATION POINT. THE UNIT PRICE BID FOR THIS ITEM WILL BE ADJUSTED BY SHELBY COUNTY TO MATCH THE FEE CHARGED BY MLGW FOR PROVIDING THE ELECTRICAL SERVICE CONNECTION.
- 2. SEE THE LATEST "CITY OF MEMPHIS STANDARD CONSTRUCTION SPECIFICATIONS" FOR TECHNICAL REQUIREMENTS.
- 3. SEE PROJECT SPECIAL PROVISIONS FOR RADAR DETECTION EQUIPMENT.
- 4. SEE CITY OF MEMPHIS SPECIFICATIONS FOR "BLUETOOTH DETECTION SYSTEM". THE INSTALLATION AT EACH LOCATION SHALL INCLUDE BLUETOOTH SENSOR, NEMA ENCLOSURE, CONDUIT AND RISER FROM CONTROLLER CABINET TO SIGNAL POLE, POWER OVER ETHERNET SUBSYSTEM, ANTENNA, ETHERNET CABLE, AND ALL OTHER CABLING, CONNECTIONS AND HARDWARE TO COMPLETE THE INSTALLATION OF A FULLY FUNCTIONAL BLUETOOTH DETECTION SYSTEM ON THE EXISTING SIGNAL POLE WHICH IS DENOTED ON THE PLANS. THIS LUMP SUM ITEM ALSO INCLUDES THE BLUETOOTH SOFTWARE LICENSE FEE FOR ALL INSTALLED UNITS. THE LUMP SUM PRICE INCLUDES ALL SOFTWARE AND HARDWARE INSTALLATION AND INTEGRATION WORK TO PROVIDE A FULLY FUNCTIONAL BLUETOOTH SYSTEM THAT ALLOWS MONITORING AND RETRIEVAL OF TRAVEL TIME AND SPEED DATA REMOTELY.
- 5. QUAZITE BRAND (MODEL NO. PG2436BB24 WITH PG2436HH6L COVER) OR APPROVED EQUIVALENT. COST INCLUDES ALL LABOR AND MATERIALS (REMOVING AND REPLACING NECESSARY SIDE WALK PANELS, REPAIR LANDSCAPING, REMOVING EXISTING PULL BOX, AND OTHER MISCELLANEOUS MATERIALS) TO COMPLETE PULL BOX INSTALLATION.
- 6. QUAZITE BRAND (MODEL NO. PG3048BB36 WITH PG3048HS6L COVER) OR APPROVED EQUIVALENT. COST INCLUDES ALL LABOR AND MATERIALS (REMOVING AND REPLACING NECESSARY SIDE WALK PANELS, REPAIR LANDSCAPING, REMOVING EXISTING PULL BOX, AND OTHER MISCELLANEOUS MATERIALS) TO COMPLETE PULL BOX INSTALLATION.
- 7. CONTRACTOR RESPONSIBLE FOR ALL COST ASSOCIATED WITH POWER CONNECTION FOR TRAFFIC SIGNAL OR RDS UNIT FROM THE DEMARCATION POINT TO THE CABINET.
- 8. CONTRACTOR SHALL INSTALL A TRACER WIRE WITH THE FIBER OPTIC CABLE FOR ALL CONDUIT ROUTING. TRACER WIRE SHALL BE 10 AWG STRANDED COPPER CONDUCTOR CABLE WITH BOTH THHN AND THWN RATINGS AND YELLOW IN COLOR.
- 9. TO BE ITERIS VANTAGE SYSTEM OR APPROVED EQUIVALENT. INCLUDES DETECTION CAMERAS, PROCESSOR UNIT, CARD RACK, POWER SUPPLY UNIT, 10" COLOR LCD MONITOR, MOUSE, VIDEO REMOTE MANAGEMENT CARD WITH ETHERNET INTERFACE AND ALL OTHER CABLING, CONNECTIONS AND HARDWARE TO COMPLETE THE INSTALLATION OF A FULLY FUNCTIONAL VIDEO DETECTION SYSTEM.
- 10. INSTALL ONE (1) DETECTOR CARD PER INTERSECTION APPROACH WHERE ADVANCE DETECTION LOOPS ARE TO BE REPAIRED OR REPLACED. SEE INTERSECTION LAYOUT SHEETS.
- 11. TO BE GTT OPTICOM SYSTEM OR APPROVED EQUIVALENT. INCLUDES OPTICAL DETECTORS, CONFIRMATION LAMPS (PAR 90), POLE-MOUNTED BEACONS, FOUR-CHANNEL PHASE SELECTOR, CARD RACK (OPTICOM 760) AND ALL CABLING, CONNECTIONS AND HARDWARE TO COMPLETE THE INSTALLATION OF A FULLY-FUNCTIONAL PREEMPTION SYSTEM, INCLUDING FIELD FINE-TUNING.
- 12. THE TRAFFIC SIGNAL CONTROLLER SHALL BE AN EAGLE EPAC M52 KEYBOARD UNIT OR APPROVED EQUIVALENT WITH NTCIP COMPLIANT SOFTWARE AND SEPAC, BUILT-IN ETHERNET PORT AND BUILT-IN STRETCH AND DELAY FEATURES FOR EACH PHASE. THE TRAFFIC CONTROLLER INSTALLATION ALONG WITH ALL AUXILIARY EQUIPMENT TO BE INSTALLED IN THE CABINET SHALL BE MANUFACTURED, SUPPLIED AND INSTALLED IN ACCORDANCE WITH THE LATEST CITY OF MEMPHIS TRAFFIC SIGNAL CONTROLLER AND CABINET SPECIFICATIONS. THE INSTALLATION SHALL HAVE A 12-CHANNEL MALFUNCTION MONITOR UNIT INSTALLED AS MODEL EDI SSM12LEIP.
- 13. FOR USE WHERE AND AS DIRECTED BY THE ENGINEER. INCLUDES REMOVAL OF EXISTING CURB RAMP, SIDEWALK, CURB, AND GUTTER AS REQUIRED, AND CONSTRUCTION OF NEW SIDEWALK AND RAMP WITH LANDING AREA AND TRANSITIONS.
- 14. ITEM TO INCLUDED ALL MATERIALS AND LABOR NECESSARY FOR INSTALLATION AND CONNECTION OF SOLAR POWER TO RDS UNIT.
- 15. FOR-POST TYPE CABLE MARKERS USED IN INTERCHANGES AND OPEN AREAS.
- 16. ITEM TO INCLUDED REMOVAL OF ALL EXISTING SIGNAL EQUIPMENT AS SHOWN IN PLANS. INCLUDES BUT IS NOT LIMITED TO REMOVAL OF SIGNAL CABINET, SIGNAL HEADS, WIRING, ETC. MEASURED ON A PER EACH INTERSECTION WHERE EQUIPMENT REMOVAL IS REQUIRED.
- 17. ITEM TO INCLUDE ALL MATERIALS NESSARY TO ATTACH CONDUIT TO BRIDGE FOR EVP SYSTEM EQUIPMENT INSTALLATION. INCLUDES WRAP AROUND CABLE MARKERS AT 100 FOOT SPACING.
- 18. ITEM TO INCLUDE ALL MATERIALS NESSARY TO ATTACH CONDUIT TO BRIDGE. INCLUDES WRAP AROUND CABLE MARKERS AT 100 FOOT SPACING.
- 19. SEE CITY OF MEMPHIS SPECIFICATIONS FOR "RUGGEDIZED ETHERNET CABINET SWITCH".
- 20. SEE CITY OF MEMPHIS SPECIFICATIONS FOR "RUGGEDIZED ETHERNET HUB SWITCH".
- 21. SEE CITY OF MEMPHIS SPECIFICATIONS FOR "SERIAL DEVICE SERVER".
- 22. SEE PROJECT SPECIAL PROVISIONS FOR UTILITY CABINETS. TYPE "A" CABINET SHALL BE UTILIZED AS PRIMARY RDS CABINET. TYPE "D" CABINET SHALL BE UTILIZED AS SECONDARY RDS CABINET.
- 23. SEE CITY OF MEMPHIS SPECIFICATIONS FOR "FIELD HUB CABINET".

STANDARD ROADWAY DRAWINGS

DWG. NO REV. DESCRIPTIONTDOT ROADWAY DESIGN STANDARDS

ROADWAY AND PAVEMENT APPURTENANCES

RP-S-7 06-04-13 DETAILS FOR STANDARD CONCRETE SIDEWALKS

TRAFFIC CONTROL

| T-FAB-1 | 05-27-97 | FLASHING YELLOW ARROW BOARD |
|---------|----------|--|
| T-FO-2 | | FIBER OPTIC UNDERGROUND ENTRANCE DETAILS |
| T-FO-4 | | FIBER OPTIC PULL BOX, CABINET & POLE DETAILS |
| T-L-1 | 12-04-13 | STANDARD LIGHTING FOUNDATION DETAILS |
| T-SG-2 | 07-29-04 | LOOP LEAD-INS, CONDUIT AND PULL BOXES |
| T-SG-3A | | ALTERNATE DETECTION DETAILS |
| T-SG-10 | 06-11-14 | MAST ARM POLE AND STRAIN POLES FOUNDATION DETAILS |
| T-WZ-10 | 04-02-12 | ADVANCE ROAD WORK SIGNING ON HIGHWAYS AND FREEWAYS |
| T-WZ-11 | 03-13-09 | ONE LANE CLOSURE DETAIL ON DIVIDED HIGHWAYS |
| T-WZ-18 | 03-13-09 | SHOULDER CLOSURE DETAIL FOR FREEWAYS AND DIVIDED HIGHWAYS |
| T-WZ-50 | 04-02-12 | TRAFFIC CONTROL FOR SIGNALS ONLY PROJECTS ON 2 OR 3 LANE MAJOR ROUTES |
| T-WZ-51 | 04-02-12 | TRAFFIC CONTROL FOR SIGNALS ONLY PROJECTS ON 4 OR 5 LANE MAJOR ROUTES |
| T-WZ-52 | 04-02-12 | TRAFFIC CONTROL FOR SIGNALS ONLY PROJECTS ON 4 OR 5 LANE MAJOR AND MINOR ROUTES |
| T-WZ-53 | 04-02-12 | TRAFFIC CONTROL FOR SIGNALS ONLY PROJECTS ON 4 OR MORE LANE DIVIDED MAJOR ROUTES |
| T-WZ-54 | 04-02-12 | TRAFFIC CONTROL FOR SIGNALS ONLY PROJECTS ON 4 OR MORE LANE DIVIDED MAJOR ROUTES AND 4 OR MORE LANE MINOR ROUTES |
| T-WZ-55 | | SIDEWALK TRAFFIC CONTROL |

CITY OF MEMPHIS DESIGN STANDARDS

TRAFFIC SIGNAL DETAILS

T/S-1 CONTROLLER CABINET AND RISER INSTALLATION DETAILS

T/S-4 SIGNAL HEAD MOUNTING STANDARDS

T/S-7 GOUNDING AND BOUNDING

T/S-8 FOUNDATION DETAILS


T/S-9 PULL BOXES, SPLICING, AND CABLE DETAILS

CIVIL DETAILS

7A CURB RAMP WITH DETECTABLE WARNING SURFACE

FOR NEW CONSTRUCTION

8 CURB RAMP IN EXISTING CONDITIONS




POWERS HILL DESIGN

IVIL ENGINEERING. CIVIL RESPONSIBILITY.

Solutions you can build upon

N_ NEEL-SCHAFFER



DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.
ESTIMATED QUANTITIES &
STANDARD DRAWINGS

SURVEY: N/A DATE: N/A BOOK: N/A
DRAFTED: DATE: 04/14 SCALE: N.T.S.
DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14

____ SHEET 2 OF 50

GENERAL NOTES

UTILITIES

- (1) THE CONTRACTOR SHALL NOTIFY EACH INDIVIDUAL UTILITY OWNER OF THEIR PLAN OF OPERATION IN THE AREA OF THE UTILITIES. PRIOR TO COMMENCING WORK, THE CONTRACTOR SHALL CONTACT THE UTILITY OWNERS AND REQUEST THEM TO PROPERLY LOCATE THEIR RESPECTIVE UTILITY ON THE GROUND. THIS NOTIFICATION SHALL BE GIVEN AT LEAST THREE (3) BUSINESS DAYS PRIOR TO COMMENCEMENT OF OPERATIONS AROUND THE UTILITY.
- (2) IT IS THE CONTRACTOR'S RESPONSIBILTY TO LOCATE AND AVOID ALL UTILITIES AND UNDERGROUND STRUCTURES. THE CONTRACTOR SHOULD NOTE THAT EXISTING GAS LINES, WATER LINES, STORM DRAINAGE AND SANITARY SEWER STRUCTURES, AND OTHER UTILITIES MAY BE PRESENT.
- (3) THE CONTRACTOR SHALL CONTACT THE CITY OF MEMPHIS SIGNAL SHOP AT 901-528-2844 FOR LOCATION OF SIGNAL CONDUIT AND WIRES.
- (4) EXISTING UTILITY LOCATIONS, AS SHOWN ON THESE PLANS, WERE COMPILED BASED ON INFORMATION AVAILABLE TO THE ENGINEER. UTILITY LOCATIONS SHOWN ARE APPROXIMATE AND ARE NOT INTENDED TO BE EXACT OR COMPLETE.
- (5) SOME UTILITIES CAN BE LOCATED BY CALLING THE TENNESSEE ONE CALL SYSTEM, INC. BY DIALING 811 (TENNESSEE 811). THE CONTRACTOR SHALL CALL THE TENNESSEE ONE CALL SYSTEM, INC. AT LEAST 72 HOURS, BUT NOT MORE THAN FIVE (5) DAYS PRIOR TO ANY PLANNED EXCAVATION BY THE CONTRACTOR.

MISCELLANEOUS

- THE LOCATIONS OF ALL NEW PULL BOXES AND CABINETS ARE SCHEMATIC.
 ADDITIONAL PULL BOXES MAY BE REQUIRED FOR BORING UNDER DRIVEWAYS. THE ENGINEER SHALL APPROVE THE FINAL LOCATIONS OF ALL PULL BOXES IN THE FIELD. THE CONTRACTOR SHALL PROVIDE AS-BUILT DOCUMENTATION (RED-LINE OF PLAN SET) WHICH SHOWS EXACT, FINAL DIMENSIONS BETWEEN PULL BOXES AND OTHER POINTS OF CONDUIT TERMINATION.
- (7) CONTACT THE APPROPRIATE JURISDICTION IN WHICH THE WORK IS BEING DONE AT LEAST 72 HOURS BEFORE BEGINNING ANY WORK ON THIS PROJECT.
- (8) SIGNAL EQUIPMENT AND INSTALLATION SHALL COMPLY WITH THE CITY OF MEMPHIS TRAFFIC SIGNAL SPECIFICATIONS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING THE SIGNAL TIMING IN THE CONTROLLER. CONTACT JAMES COLLINS, KIMLEY-HORN AND ASSOCIATES, INC. AT (901) 374-9109 A MINIMUM OF THIRTY (30) DAYS PRIOR TO ACTIVATION TO OBTAIN TIMINGS.
- (10) ALL SALVAGEABLE ITEMS TO BE DELIVERED TO THE JURISDICTION IN WHICH THE WORK IS BEING DONE.
- (11) THE CONTRACTOR SHALL BRING THE NEW CONTROLLER UNITS AND THE SIGNAL TIMING SHEETS TO THE CITY OF MEMPHIS TRAFFIC SIGNAL MAINTENANCE OFFICE FOR REVIEW PRIOR TO INSTALLATION OF THE CONTROLLERS IN THE CABINET.
- (12) THE CONTRACTOR SHALL COIL 50' OF (EACH) FIBER OPTIC CABLE IN ALL FIBER OPTIC PULL BOXES.
- (13) CONTRACTOR SHALL HAVE SIGNAL MAINTENANCE RESPONSIBILITY OF THE INTERSECTION ONCE WORK ON EACH INTERSECTION HAS BEGUN. THE RESPONSIBILITY SHALL EXTEND TO CONTRACT ITEMS ONLY AND SHALL END UPON SUBSTANTIAL COMPLETION AND ACCEPTANCE OF THE WORK AT THE INTERSECTION.
- (14) THE CONTRACTOR SHALL NOT SPLICE ANY VIDEO DETECTION OR EVP EQUIPMENT CABLES.
- (15) THE CONTRACTOR SHALL INSTALL EVP EQUIPMENT THAT INCLUDES MULTI-MODE GPS/IR AT INTERSECTIONS IN CITY OF MEMPHIS AND CITY OF GERMANTOWN.

CABLE MARKER NOTES

- (16) THE CONTRACTOR SHALL INSTALL CABLE MARKERS TO IDENTIFY THE DETECTION AND EMERGENCY VEHICLE PREEMPTION CABLES. LEGENDS AND COLORS FOR MARKERS ARE TO APPEAR ACCORDING TO THE INFORMATION SUPPLIED BY THE CITY OF MEMPHIS SIGNAL MAINTENANCE DEPARTMENT. MARKERS ARE TO BE PERMANENT, BRIGHTLY COLORED, NON-REFLECTIVE, WITH BLACK LETTERING. MARKERS ARE TO BE MANUFACTURED OF PLASTIC, VINYL OR FIBERGLASS MATERIAL THAT IS DURABLE, UV LIGHT-RESISTANT, WEATHER-PROOF AND SCRATCH-RESISTANT.
- CURB MARKERS SHALL BE INSTALLED TO IDENTIFY CABLES THAT ARE IN OR NEAR THE STREET. CURB MARKERS ARE TO BE FOUR-INCH DIAMETER ROUND DISKS APPLIED TO CONCRETE OR METAL SURFACES WITH AN ADHESIVE ACCORDING TO THE RECOMMENDATION OF THE MANUFACTURER. CURB MARKERS ARE TO BE INSTALLED ON CABINET AND POLE FOUNDATIONS ON THE SIDE ABOVE THE CABLE. CURB MARKERS ARE ALSO TO BE PLACED ON THE CURB AT 100-FOOT SPACING ALONG ANY RUN OF CABLE THAT IS PARALLEL TO THE CURB. WHERE PAVED SHOULDER EXIST INSTEAD OF CURB, PLACE CURB MARKERS ON THE PAVEMENT SURFACE ONE FOOT FROM THE EDGE OF THE SURFACE, OR DIRECTLY OVER THE CONDUIT OR CABLE. CURB MARKERS ARE TO BE DURACAST STYLE CURB MARKERS AS MADE BY DAS MANUFACTURING, WILLIAM FRICK AND CO., OR APPROVED EQUAL. CURB MARKERS SHALL BE ABRASION AND UV-RESISTANT.

(18) POST-TYPE CABLE MARKER SHALL BE UTILIZED IN INTERCHANGE AREAS AND OTHER LOCATIONS WHERE USE OF CURB MARKERS IS IMPRACTICAL WITHIN THESE AREAS. POST-TYPE MARKERS SHALL BE INSTALLED ADJACENT TO ALL PULLBOXES AND AT APPROXIMATELY 250 FT SPACING BETWEEN PUBLLBOXES. MARKER POSTS SHALL BE 60 INCHES IN LENGTH, 3.5 INCHES IN WIDTH (MINIMUM) AND CONSTRUCTED OF UV RESISTANT FIBERGLASS COMPOSITE MATERIAL. POST COLOR AND LEGEND SHALL BE SUSTANTIALLY SIMILAR TO CURB MARKERS USED ELSEWHERE ON THE PROJECT.

SPECIAL NOTES

GENERAL

(1) NOTHING IN THE GENERAL NOTES OR SPECIAL PROVISIONS SHALL RELIEVE THE CONTRACTOR FROM HIS RESPONSIBILITIES TOWARD THE SAFETY AND CONVENIENCE OF THE GENERAL PUBLIC AND THE RESIDENTS ALONG THE PROPOSED CONSTRUCTION AREA.

WORK ZONE TRAFFIC CONTROL


- (2) ADVANCED WARNING SIGNS SHALL NOT BE DISPLAYED MORE THAN FORTY-EIGHT (48) HOURS BEFORE PHYSICAL CONSTRUCTION BEGINS. SIGNS MAY BE ERECTED UP TO ONE WEEK BEFORE NEEDED, IF THE SIGN FACE IS FULLY COVERED.
- (3) IF THE CONTRACTOR MOVES OFF THE PROJECT, HE SHALL COVER OR REMOVE ALL UNNEEDED SIGNS AS DIRECTED BY THE ENGINEER. COSTS OF REMOVAL, COVERING, AND REINSTALLING SIGNS SHALL NOT BE MEASURED AND PAID FOR SEPARATELY, BUT ALL COSTS SHALL BE INCLUDED IN THE PRICE BID FOR OTHER ITEMS OF WORK.
- (4) A LONG TERM BUT SPORADIC USE WARNING SIGN, SUCH AS A FLAGGER SIGN, MAY REMAIN IN PLACE WHEN NOT REQUIRED PROVIDED THE SIGN FACE IS FULLY COVERED.
- (5) TRAFFIC CONTROL DEVICES SHALL NOT BE DISPLAYED OR ERECTED UNLESS RELATED CONDITIONS ARE PRESENT NECESSITATING WARNING.
- (6) USE OF BARRICADES, PORTABLE BARRIER RAILS, VERTICAL PANELS, AND DRUMS SHALL BE LIMITED TO THE IMMEDIATE AREAS OF CONSTRUCTION WHERE A HAZARD IS PRESENT. THESE DEVICES SHALL NOT BE STORED ALONG THE ROADWAY WITHIN THIRTY (30) FEET OF THE EDGE OF THE TRAVELED WAY BEFORE OR AFTER USE UNLESS PROTECTED BY GUARDRAIL, BRIDGE RAIL, AND/OR BARRIERS INSTALLED FOR OTHER PURPOSES. THESE DEVICES SHALL BE REMOVED FROM THE CONSTRUCTION WORK ZONE WHEN THEY ARE NO LONGER NEEDED. WHERE THERE IS INSUFFICIENT RIGHT-OF-WAY TO PROVIDE FOR THIS REQUIRED SETBACK, THE CONTRACTOR SHALL DETERMINE THE ALTERNATE LOCATIONS AND REQUEST THE ENGINEER'S APPROVAL TO USE THEM.
- (7) THE CONTRACTOR SHALL NOT BE PERMITTED TO PARK ANY VEHICLES OR CONSTRUCTION EQUIPMENT DURING PERIODS OF INACTIVITY, WITHIN THIRTY (30) FEET OF THE EDGE OF PAVEMENT WHEN THE LANE IS OPEN TO TRAFFIC UNLESS PROTECTED BY GUARDRAIL, BRIDGE RAIL, AND/OR BARRIERS INSTALLED FOR OTHER PURPOSES. WHERE THERE IS INSUFFICIENT RIGHT-OF-WAY TO PROVIDE FOR THIS REQUIRED SETBACK, THE CONTRACTOR SHALL DETERMINE THE ALTERNATE LOCATIONS AND REQUEST THE ENGINEER'S APPROVAL TO USE THEM.
- (8) ALL DETOUR AND CONSTRUCTION SIGNING SHALL BE IN STRICT ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
- (9) CONTRACTOR SHALL EXPEDITE REPLACEMENT OF SIGNAL CONTROLLERS AND CABINETS TO MINIMIZE DELAYS ON THE PUBLIC. CONTRACTOR SHALL EMPLOY OFF-DUTY POLICE TO PROVIDE ADDITIONAL TRAFFIC CONTROL DURING TIMES WHEN INTERSECTION IS DARK. TRANSFER SHALL BE ACCOMPLISHED BETWEEN THE HOURS OF 9:00 AM AND 3:00 PM OR BETWEEN 7:00 PM AND 5:00 AM. COST OF POLICE MANPOWER TO BE INCLUDED IN OTHER ITEMS.
- (10) LANES CLOSURES DURING MAINTENANCE OF TRAFFIC SHALL BE COORDINATED WITH AND APPROVED BY CITY TRAFFIC ENGINEER PRIOR TO BEGINNING WORK ACTIVITY. IN GENERAL, LANE CLOSURES SHALL NOT BE USED ON WEEKDAYS BETWEEN 7:00 AM-9:00 AM OR 4:00 PM-6:00 PM. LANE CLOSURES MAY BE FURTHER LIMITED BY CITY TRAFFIC ENGINEER AT SPECIFIC LOCATIONS.
- (11) OPENINGS IN SIDEWALKS SHALL BE BARRICADED WITH DETECTABLE PEDESTRIAN BARRICADES (IN ACCORDANCE WITH MUTCD SECTION 6F.74) UNTIL RESTORATION CAN BE ACCOMPLISHED. OPENINGS SHALL BE RESTORED AS QUICKLY AS POSSIBLE. IF SIDEWALK WIDTH DOES NOT PERMIT A MINIMUM 48 INCH PATH OF TRAVEL AROUND THE WORK AREA, THE ENTIRE SIDEWALK SEGMENT MUST BE CLOSED WITH A FULL-WIDTH CANE-DETECTABLE BARRICADE AND AN ALTERNATE PATH OF TRAVEL PROVIDED. TEMPORARY RESTORATION WITH FIRMLY-COMPACTED GRAVEL BACKFILL, METAL PLATES OR TEMPORARY PLYWOOD WALKWAY MAY BE UTILIZED UNTIL PERMANENT RESTORATION CAN BE ACCOMPLISHED. ANY TEMPORARY SURFACE MUST BE AT LEAST 48 INCHES WIDE, STABLE, SLIP-RESISTANT, AND FREE FROM ANY VERTICAL DISCONTINUITITES GREATER THAN ½ INCH (BEVELED). ANY SIDEWALK OPENINGS SHALL BE PERMANENTLY RESTORED WITHIN FIVE WORKING DAYS OF THE TIME THE OPENING IS CREATED, UNLESS A SPECIFIC REQUEST BY THE CONTRACTOR IS APPROVED BY THE ENGINEER.

EROSION PREVENTION AND SEDIMENT CONTROL

- (12) ALL COSTS FOR EROSION PREVENTION AND SEDIMENT CONTROL WORK SHALL BE INCLUDED IN THE LUMP-SUM PRICE BID FOR EROSION AND SILTATION CONTROL. THIS SHALL INCLUDE ALL LABOR, MATERIALS, AND EQUIPMENT NECESSARY TO PROVIDE TEMPORARY STABLIZATION OF DISTURBED AREAS, CONTAIN SEDIMENT WITH THE WORK AREA, AND PREVENT POLLUTANTS FROM ENTERING WATERS OF THE STATE/US.
- (13) CLEARING, GRUBBING, AND OTHER DISTURBANCE TO EXISTING VEGETATION SHALL BE LIMITED TO THE MINIMUM NECESSARY FOR SLOPE CONSTRUCTION AND EQUIPMENT OPERATIONS. EXISTING VEGETATION SHOULD BE PRESERVED TO THE MAXIMUM EXTENT POSSIBLE. UNNECESSARY VEGETATION REMOVAL IS PROHIBITED.
- (14) THE CONTRACTOR SHALL ESTABLISH AND MAINTAIN A PROACTIVE METHOD TO PREVENT THE OFF-SITE MIGRATION OR DEPOSIT OF SEDIMENT ON ROADWAYS USED BY THE GENERAL PUBLIC. IF SEDIMENT ESCAPES THE CONSTRUCTION SITE, OFF-SITE ACCUMULATIONS OF SEDIMENT THAT HAVE NOT REACHED A STREAM MUST BE REMOVED AT A FREQUENCY SUFFICIENT TO MINIMIZE OFF-SITE IMPACTS (E.G., FUGITIVE SEDIMENT THAT HAS ESCAPED THE CONSTRUCTION SITE AND HAS COLLECTED IN A STREET MUST BE REMOVED SO THAT IT IS NOT SUBSEQUENTLY WASHED INTO STORM SEWERS AND STREAMS BY THE NEXT RAIN AND/OR SO THAT IT DOES NOT POSE A SAFETY HAZARD TO USERS OF PUBLIC STREETS). ARRANGEMENTS CONCERNING REMOVAL OF SEDIMENT ON ADJOINING PROPERTY MUST BE SETTLED WITH THE ADJOINING PROPERTY OWNER BEFORE REMOVAL OF SEDIMENT.
- (15) WATER PUMPED FROM WORK AREAS AND EXCAVATION MUST BE HELD IN SETTLING BASINS OR TREATED BY FILTRATION OR CHEMICAL TREATMENT PRIOR TO ITS DISCHARGE INTO SURFACE WATERS. ALL PHYSICAL AND/OR CHEMICAL TREATMENT WILL BE APPLIED IN ACCORDANCE WITH MANUFACTURER'S GUIDELINES AND FULLY DESCRIBED IN THE EPSC PLANS. WATER MUST BE HELD IN SETTLING BASINS UNTIL AT LEAST AS CLEAR AS THE RECEIVING WATERS. SETTLING BASINS SHALL NOT BE LOCATED CLOSER THAN 20 FEET FROM THE TOP BANK OF A STREAM. SETTLING BASINS AND SEDIMENT TRAPS SHALL BE PROPERLY DESIGNED ACCORDING TO THE SIZE OF THE DRAINAGE AREAS OR VOLUME OF WATER TO BE TREATED. TREATED WATER MUST BE DISCHARGED THROUGH A PIPE OR WELL- VEGETATED OR LINED CHANNEL, SO THAT THE DISCHARGE DOES NOT CAUSE EROSION OR SEDIMENT TRANSPORT. DISCHARGES FROM BASINS AND IMPOUNDMENTS SHALL UTILIZE OUTLET STRUCTURES THAT ONLY WITHDRAW WATER FROM NEAR THE SURFACE OF THE BASIN OR IMPOUNDMENT. DISCHARGES MUST NOT CAUSE AN OBJECTIONABLE COLOR CONTRAST WITH THE RECEIVING STREAM.
- (16) IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO PROTECT FROM EROSION ANY EXPOSED EARTH RESULTING FROM TRENCHING AND EXCAVATION, AND TO PROVIDE FOR CONTAINMENT OF SEDIMENT THAT MAY RESULT FROM THIS WORK. PRIOR TO BEGINNING WORK, ADEQUATE MEASURES MUST BE IN PLACE TO TRAP ANY SEDIMENT THAT MAY TRAVEL OFF-SITE IN THE EVENT OF RAIN. DURING THE PROGRESSION OF THE WORK, EXPOSED EARTH AREAS SHALL BE STABILIZED AS SOON AS POSSIBLE TO PREVENT EROSION. AT NO TIME SHALL EXPOSED EARTH RESULTING FROM THESE OPERATIONS HAVE UNPROTECTED ACCESS TO FLOWING OFF-SITE AND ENTERING WATERS OF THE STATE/U.S.
- (17) SILT FENCE OR OTHER BARRIERS OF THE SPECIFIED TYPE SHALL BE INSTALLED ON THE DOWNHILL SIDE OF STOCKPILED SOIL. POLYETHYLENE SHEETING MAY BE USED TO COVER SPOILS FROM EXCAVATION.
- (18) FOR THE INSTALLATION OF CONDUITS AND CABLES, TRENCHES SHALL BE BACKFILLED DAILY AS CONSTRUCTION PROCEEDS. BACKFILLED TRENCHES SHALL BE SEEDED AND MULCHED OR SODDED DAILY IF POSSIBLE, BUT NO LATER THAN SEVEN DAYS AFTER BEING BACKFILLED. ANY TEMPORARY SPOIL OF EXCAVATED EARTH SHALL BE LOCATED WITHIN EROSION PREVENTION AND SEDIMENT CONTROL MEASURES. IF TRENCHES ARE NOT BACKFILLED OVERNIGHT, APPROPRIATE EPSC MEASURES WILL BE INSTALLED BY THE CONTRACTOR UNTIL SUCH TIME AS THE TRENCH IS BACKFILLED.
- (19) MUD OR BORING FLUID RESULTING FROM BORING OPERATIONS MUST BE CONTAINED, REMOVED, AND DISPOSED OF PROPERLY.

RADAR DETECTION SYSTEM

(20) SOLAR POWER SYSTEMS FOR RDS UNITS SHALL CONSIST OF A SOLAR PANEL, BATTERY, CHARGE REGULATOR, AND ALL CABLING AND ACCESSORIES NECESSARY TO PROVIDE A FULLY FUNCTIONAL SOLAR POWER SYSTEM CAPABLE OF POWERING THE RDS UNIT AND ASSOCIATED COMMUNICATIONS EQUIPMENT. THE SOLAR PANEL SHALL BE SIZED BY THE MANUFACTURER TO PROVIDE THE REQUIRED OUTPUT FOR RDS OPERATION AND BATTERY CHARGING. THE BATTERY SHALL BE SIZED TO PROVIDE A MINIMUM OF 3 DAYS OF CONTINUOUS OPERATION OF THE RDS UNIT WITHOUT CHARGING.



NEEL-SCHAFFER

Solutions you can build upon

DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.
GENERAL NOTES &
SPECIAL NOTES


SURVEY: N/A DATE: N/A BOOK: N/A

DRAFTED: DATE: 04/14 SCALE: N.T.S.

DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14

JURISDICTION: SHEET 3 OF 50

| | TABULATED INTERSECTION AND RDS QUANTITES | | | | | | | | | | | | | | | | | | | | | | | |
|-------------|--|-------------------------|-----------------------------------|---|--|----------------------------|-------------------------------|-------------------------------|----------|-------------------------------|--|-------------------------------|--|---|---------------------------------|-------|--|-------------------------------------|---|---|--|--------------------------------------|------------------------|---------------------------------------|
| | LOCATION | LOCAL | CONTROLLI | ER CABINET | AND HUB C | CABINET | LOCA | L CONTRO | LLER | VID | DEO | F | FIBER OPTIC | EQUIPMEN | Т | | | | R.A | ADAR DETEC | CTION SYST | EM | | 0 - |
| DRAWING NO. | STREET 1 STREET 2 | RETAIN EXISTING CABINET | REMOVE EXITING POLE MOUNT CABINET | INSTALL NEW 8- PHASE BASE MOUNT CABINET | INSTALL CABLE IN EXISTING CONDUIT INTO CABINET | INSTALL NEW BASE MOUNT HUB | RETAIN EXISTING CONTROLLER | REMOVE EXISTING CONTROLLER | L NEW 8- | LL VIDEO LE STION SM | INSTALL 4- CHANNEL, RACK MOUNT VEHICLE DETECTOR | L ETHERNET ET SWITCH A) | INSTALL ETHERNET HUB SWITCH (TYPE B) | INSTALL FIBER DISTRIBUTION BOX IN CABINET | INSTALL SERIAL DEVICE SERVER | . – – | INSTALL WEATHERPROOF SPLICE ENCLOSURE IN PULLBOX | INTALL RADAR DETECTION SYSTEM | INSTALL NEW POLE MOUNT RDS CABINET (TYPE A) | INSTALL NEW POLE MOUNT RDS CABINET (TYPE D) | INSTALL 20' ALUMINUM PEDESTAL POLE | MLG&W POWER SERVICE CONNECTION | SOLAR POWER FOR RDS | BLUETOOTH TRAFFIC DETECTION SYSTEM |
| TUO | ITEM NUMBER | - | - | 730-15.32 | - | 725-24.11 | - | - | | | 730-13.03 | | | 730-03.31 | 725-21.22 | | 725-02.79 | 725-21.91 | 725-24.01 | | | | 725-21.97 | 725-21.88 |
| F | UNIT | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH | EACH |
| RD-01 | RDS AP-1 | | | | | | | | | | | 1 | | 1 | | 1 | 1 | 1 | 1 | | 1 | | 1 | |
| RD-01 | RDS AP-2 | | | | | | | | | | | 1 | | 1 | | 1 | 1 | 2 | 1 | 1 | 2 | | 2 | |
| RD-01 | RDS AP-3 | | | | | | | | | | | 1 | | 1 | | 1 | 1 | 1 | 1 | | 1 | | 1 | |
| IL-01 | James Rd/ Stage Rd Jackson Ave/Austin Peay Blvd | 1 | | | 1 | | 1 | | | | | 1 | | 1 | 1 | 1 | 1 | | | | | | | |
| IL-02 | Austin Peay Blvd Jones Rd | | 1 | 1 | | | | 1 | 1 | 1 | 3 | 1 | | 1 | | 1 | 1 | | | | | | | |
| IL-03 | Austin Peay Blvd Coleman Rd | | | 1 | | | | 1 | 1 | 1 | 4 | 1 | | 1 | | 1 | 1 | | | | | | | |
| RD-01 | RDS AP-4 | | | | | | | | | | | 1 | | 1 | | 1 | 1 | 1 | 1 | | 1 | | 1 | |
| IL-04 | Austin Peay Raleigh Blvd Springs Mall | 1 | | | 1 | | | 1 | 1 | 1 | | 1 | | 1 | | 1 | 1 | | | | | | | |
| IL-05 | Austin Peay Blvd Yale Rd | 1 | | | 1 | | 1 | | | 1 | | 1 | | 1 | 1 | 1 | 1 | | | | | | | 1 |
| IL-06 | James Rd/ Old Austin Stage Rd Peay Hwy | | | 1 | | | | 1 | 1 | 1 | 4 | 1 | | 1 | | 1 | 1 | | | | | | | |
| RD-02 | RDS S-1 | | | - | | | | | | | | 1 | | 1 | | 1 | 1 | 1 | 1 | | 1 | 1 | | |
| IL-07 | Stage Rd Coleman Rd | | | 1 | | | | 1 | 1 | 1 | 4 | 1 | | 1 | | 1 | 1 | | | | | | | |
| RD-02 | RDS S-2 | | | - | | | | | | | | 1 | | 1 | | 1 | 1 | 1 | 1 | | 1 | 1 | | |
| IL-08 | Stage Rd Covington Pike | | | 1 | | 1 | | 1 | 1 | 1 | 4 | 1 | 1 | 1 | | 2 | 2 | | | | | | | 1 |
| | TOTALS | 3 | 1 | 5 | 3 | 1 | 2 | 6 | 6 | 7 | 19 | 14 | 1 | 14 | 2 | 15 | 15 | 7 | 6 | 1 | 7 | 2 | 5 | 2 |



NEEL-SCHAFFER
Solutions you can build upon


DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.
SUMMARY OF WORK
BY INTERSECTION


SURVEY: N/A DATE: N/A BOOK: N/A


DRAFTED: DATE: 04/14 SCALE: N.T.S.

DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14

JURISDICTION: SHEET 4 OF 50







XXXX - INTERSECTION ID NUMBER

NOTES:


1. CABLE IDENTIFICATION IS AS SHOWN IN THE FOLLOWING EXAMPLE:

CABLE XX FIBERS XX ACTIVE

INDICATES THE NUMBER OF ACTIVE FIBERS WITHIN THE CABLE SHEATH.

3. FIBER OPTIC PULL BOXES ARE NOT SHOWN ON THIS SCHEMATIC.

WITHIN THE CABLE SHEATH.



DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.


COMMUNICATIONS CABLE SCHEMATIC & LEGEND


SURVEY: N/A DATE: N/A BOOK: N/A


DRAFTED: DATE: 04/14 SCALE: N.T.S.


DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14


JURISDICTION: SHEET 5 OF 50






















B2 REMOVE EXISTING CABINET B3 INSTALL NEW BASE MOUNTED CONTROLLER CABINET | B5 | INSTALL BASE MOUNTED HUB CABINET | B6 | INSTALL WEATHER PROOF SPLICE ENCLOSURE B7 INSTALL FIBER DISTRIBUTION BOX B9 INSTALL TRAFFIC SIGNAL PULLBOX |B10| INSTALL FIBER OPTIC PULLBOX TYPE A B11 INSTALL FIBER OPTIC PULLBOX TYPE B |B13| INSTALL 20' PEDESTAL POLE B15 MLGW POWER SERVICE CONNECTION D12 INSTALL NEW POLE MOUNTED RDS CABINET D13 INSTALL RADAR DETECTION SYSTEM D15 INSTALL NEW SECONDARY POLE MOUNTED RDS CABINET W6 SMFO CABLE W7 SMFO TRUNK CABLE W9 SMFO DROP CABLES (6-FIBER) W11 RDS CABLE /3\ INSTALL 2" RISER INTO BOTTOM OF CABINET 4\ INSTALL 2" RISER WITH WEATHERHEAD 5\ INSTALL 2" RISER WITH SEALING BUSHING 6 INSTALL 2" CONDUIT ENTRANCE INTO EXISTING FOUNDATION 7 INSTALL 2" RGS CONDUIT ON EXISTING STRUCTURE 8 INSTALL 2" CONDUIT INTO EXTERIOR OF CABINET 9\ INSTALL 2" PVC CONDUIT 10\ JACK AND BORE 2" CONDUIT /11\ INSTALL 2" RGS CONDUIT /12\ INSTALL 3" PVC CONDUIT /13\ INSTALL 3" CONDUIT ENTRANCE INTO EXISTING FOUNDATION /14\ INSTALL 3" RISER WITH WEATHERHEAD 15\ INSTALL 3" CONDUIT INTO CABINET /16\ INSTALL 3" RGS CONDUIT ON EXISTING STRUCTURE 17 JACK AND BORE 3" CONDUIT /18\ INSTALL 3" RISER INTO BOTTOM OF CABINET 19 REUSE EXISTING RISER WITH WEATHERHEAD 20\ TIE CONDUIT INTO EXISTING PULLBOX 21\ REUSE EXISTING CONDUIT 26\ INSTALL CABLES IN EXISTING POLE IN PROPOSED WEATHERHEAD 27\ INSTALL CABLES IN EXISTING WEATHERHEAD 28\ INSTALL CABLES IN EXISTING POLE 29\ INSTALL CABLES IN PROPOSED POLE 35 ATTACH CONDUIT TO BRIDGE NUMBER OF CABLES, LOOPS, ETC. X) NUMBER OF CONDUCTORS, PAIRS, ETC.

B1 RETAIN AND MODIFY EXISTING CABINET







CL-07

DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.
AUSTIN PEAY HIGHWAY


JSIIN PEAY HIG CABLE LAYOUT FROM 150+00 TO 157+00


SURVEY: N/A DATE: N/A BOOK: N/A


DRAFTED: APL DATE: 02/14 SCALE: 1"=50'


DESIGNED: APL DATE: 02/14 CHECKED: N/A DATE: N/A


JURISDICTION: ______ SHEET 13 OF 50















AUSTIN PEAY HWY @ JAMES RD

| PREE | MPT TABLE |
|----------|-----------------|
| DETECTOR | PHASE(S) CALLED |
| 2 | 2 + 6 |
| 3 | 3 + 8 |
| 6 | 2 + 6 |
| 8 | 3 + 8 |

NOTES: 1. LOOP DETECTOR AMPLIFIERS FOR ALL DETECTION TO REMAIN. 2. INSTALL DUPLEX GFI OUTLET IN EXISTING BASE MOUNT CABINET.







DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN. AUSTIN PEAY HIGHWAY AUSTIN PEAY HWY @ JAMES RD INTERSECTION LAYOUT

1L - 01

B1 RETAIN AND MODIFY EXISTING CABINET

B5 INSTALL BASE MOUNTED HUB CABINET

B7 INSTALL FIBER DISTRIBUTION BOX

B9 INSTALL TRAFFIC SIGNAL PULLBOX

B13 INSTALL 20' PEDESTAL POLE

B10 INSTALL FIBER OPTIC PULLBOX TYPE A

B11 INSTALL FIBER OPTIC PULLBOX TYPE B

B15 MLGW POWER SERVICE CONNECTION

C6 | INSTALL ETHERNET CABINET SWITCH

D2 INSTALL EVP CONFIRMATION BEACON

D3 INSTALL EVP CONFIRMATION LAMP

D8 INSTALL EVP PHASE SELECTOR

D9 INSTALL VIDEO DETECTION PROCESSOR

D12 INSTALL NEW POLE MOUNTED RDS CABINET

D16 INSTALL BLUETOOTH DETECTION SYSTEM

| W2 | EVP CONFIRMATION BEACON POWER CABLE(S)

| W3 | EVP CONFIRMATION LAMP POWER CABLE(S)

3 INSTALL 2" RISER INTO BOTTOM OF CABINET

 $\sqrt{6}$ Install 2" conduit entrance into existing foundation

/13\ INSTALL 3" CONDUIT ENTRANCE INTO EXISTING FOUNDATION

/25\ INSTALL CABLES IN EXISTING POLE IN EXISTING WEATHERHEAD

26 INSTALL CABLES IN EXISTING POLE IN PROPOSED WEATHERHEAD

/16\ INSTALL 3" RGS CONDUIT ON EXISTING STRUCTURE

/32\ LASH TO EXISTING MESSENGER WIRE/SPANWIRE

D13 INSTALL RADAR DETECTION SYSTEM

D14 VIDEO REMOTE MANAGEMENT CARD

| W1 | EVP DETECTOR CABLE(S)

W4 VIDEO DETECTOR CABLE(S)

W5 2C DETECTOR CABLE(S)

W9 DROP CABLES (6-FIBER)

9 INSTALL 2" PVC CONDUIT

11 INSTALL 2" RGS CONDUIT

12 INSTALL 3" PVC CONDUIT

28 INSTALL CABLES IN EXISTING POLE

35 ATTACH CONDUIT TO BRIDGE

10 JACK AND BORE 2" CONDUIT

W7 SMFO TRUNK CABLE

W6 SMFO CABLE

W11 RDS CABLE

C2 | INSTALL 8-PHASE CONTROLLER

| C7 | INSTALL SERIAL DEVICE SERVER

C8 INSTALL ETHERNET HUB SWITCH

D1 INSTALL EVP DETECTOR

B6 INSTALL WEATHER PROOF SPLICE ENCLOSURE

B3 INSTALL NEW BASE MOUNTED CONTROLLER CABINET

C4 REMOVE EXISTING CONTROLLER AND INSTALL NEW CONTROLLER

D5 INSTALL VIDEO DETECTION CAMERA WITH TYPE 2 MOUNT


| D6 | INSTALL VIDEO DETECTION CAMERA WITH TYPE 3 MOUNT

D10 INSTALL DETECTOR AMPLIFIER (4-CHANNEL) IN CABINET

B2 REMOVE EXISTING CABINET

DATE: N/A BOOK: N/A SCALE: 1"=30' SURVEY: N/A DRAFTED: DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14 JURISDICTION: ____ _____ SHEET 18 OF 50

POWERS HILL DESIGN CIVIL RESPONSIBILITY. NEEL-SCHAFFER
Solutions you can build upon



1. EXISTING SIGNAL CABLE WIRING (3-5c, 1-7c, AND 2-2sc) SHALL BE EXTENDED

2. COST FOR INSTALLATION OF PROPOSED WEATHERHEAD SHALL BE ABSORBED IN

TO PROPOSED BASE MOUNT CABINET LOCATION.

3. SEE DETAIL SHEET D-03 FOR TYPICAL COUNT ZONE DETAIL.

COST OF OTHER ITEMS.

POWERS HILL DESIGN
CIVIL ENGINEERING. CIVIL RESPONSIBILITY.

NEEL-SCHAFFER
Solutions you can build upon

GRAPHIC SCALE

SIGNAL SYSTEM PROJECT SET #8

SHELBY COUNTY, TN.

AUSTIN PEAY HIGHWAY


JONES RD INTERSECTION LAYOUT

SURVEY: N/A DATE: N/A BOOK: N/A

DRAFTED: DATE: 04/14 SCALE: 1"=30"

DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14

JURISDICTION: SHEET 19 OF 50




CIVIL ENGINEERING. CIVIL RESPONSIBILITY.

SURVEY: N/A DATE: N/A BOOK: N/A

DRAFTED: DATE: 04/14 SCALE: 1"=30'

DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14

JURISDICTION: SHEET 20 OF 50



NUMBER OF CABLES, LOOPS, ETC.

X) NUMBER OF CONDUCTORS, PAIRS, ETC.

1. REMOVE UNUSED DETECTOR CABLES FROM CABINET TO NEAREST PULL BOX OR

3. REMOVE EXISTING CONTROLLER.

2. REMOVE UNUSED LOOP DETECTOR HARNESSES.

REMOVAL NOTES:

POLE BASE.

REVISIONS DESCRIPTIONS APPROVED

DIVISION OF PUBLIC WORKS CONGESTION MANAGEMENT PROGRAM SIGNAL SYSTEM PROJECT SET #8 SHELBY COUNTY, TN. AUSTIN PEAY HIGHWAY RALEIGH SPRINGS MALL INTERSECTION LAYOUT

B1 RETAIN AND MODIFY EXISTING CABINET

| B5 | INSTALL BASE MOUNTED HUB CABINET

B7 | INSTALL FIBER DISTRIBUTION BOX

B9 INSTALL TRAFFIC SIGNAL PULLBOX

B13 INSTALL 20' PEDESTAL POLE

B15 MLGW POWER SERVICE CONNECTION

C6 | INSTALL ETHERNET CABINET SWITCH

D2 INSTALL EVP CONFIRMATION BEACON

D3 INSTALL EVP CONFIRMATION LAMP

D8 INSTALL EVP PHASE SELECTOR

D9 INSTALL VIDEO DETECTION PROCESSOR

D13 INSTALL RADAR DETECTION SYSTEM

D14 VIDEO REMOTE MANAGEMENT CARD

W1 EVP DETECTOR CABLE(S)

| W4 | VIDEO DETECTOR CABLE(S)

W5 2C DETECTOR CABLE(S)

W7 SMFO TRUNK CABLE

W9 DROP CABLES (6-FIBER)

9\ INSTALL 2" PVC CONDUIT

/11\ INSTALL 2" RGS CONDUIT

12 INSTALL 3" PVC CONDUIT

28 INSTALL CABLES IN EXISTING POLE

35\ ATTACH CONDUIT TO BRIDGE

/10\ JACK AND BORE 2" CONDUIT

W6 SMFO CABLE

W11 RDS CABLE

D12 INSTALL NEW POLE MOUNTED RDS CABINET

D16 INSTALL BLUETOOTH DETECTION SYSTEM

| W2 | EVP CONFIRMATION BEACON POWER CABLE(S)

W3 EVP CONFIRMATION LAMP POWER CABLE(S)

 $\sqrt{3}$ INSTALL 2" RISER INTO BOTTOM OF CABINET

6 INSTALL 2" CONDUIT ENTRANCE INTO EXISTING FOUNDATION

/13\ INSTALL 3" CONDUIT ENTRANCE INTO EXISTING FOUNDATION

/25\ INSTALL CABLES IN EXISTING POLE IN EXISTING WEATHERHEAD

26\ INSTALL CABLES IN EXISTING POLE IN PROPOSED WEATHERHEAD

16\ INSTALL 3" RGS CONDUIT ON EXISTING STRUCTURE

/32\ LASH TO EXISTING MESSENGER WIRE/SPANWIRE

C2 INSTALL 8-PHASE CONTROLLER

C7 INSTALL SERIAL DEVICE SERVER

C8 INSTALL ETHERNET HUB SWITCH

D1 INSTALL EVP DETECTOR

B10 INSTALL FIBER OPTIC PULLBOX TYPE A

B11 INSTALL FIBER OPTIC PULLBOX TYPE B

B6 INSTALL WEATHER PROOF SPLICE ENCLOSURE

B3 INSTALL NEW BASE MOUNTED CONTROLLER CABINET

C4 REMOVE EXISTING CONTROLLER AND INSTALL NEW CONTROLLER

D5 INSTALL VIDEO DETECTION CAMERA WITH TYPE 2 MOUNT

D6 INSTALL VIDEO DETECTION CAMERA WITH TYPE 3 MOUNT

D10 INSTALL DETECTOR AMPLIFIER (4-CHANNEL) IN CABINET


B2 REMOVE EXISTING CABINET

DATE: N/A BOOK: N/A SCALE: 1"=30" SURVEY: N/A DRAFTED: _ DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14 JURISDICTION: _____ _____ SHEET 21 OF 50

1L - 04

POWERS HILL DESIGN CIVIL RESPONSIBILITY. NEEL-SCHAFFER
Solutions you can build upon

- ADVANCE DETECTION TO REMAIN.
- 2. INSTALL DUPLEX GFI OUTLET IN EXISTING BASE MOUNT CABINET.
- 3. MODIFY DETECTOR WIRING FOR INSTALLATION OF VIDEO DETECTION SYSTEM.
- 4. SEE DETAIL SHEET D-03 FOR TYPICAL COUNT ZONE DETAIL.



6. SEE DETAIL SHEET D-03 FOR TYPICAL COUNT ZONE DETAIL.

 SURVEY: N/A
 DATE: N/A
 BOOK: N/A

 DRAFTED:
 DATE: 04/14
 SCALE: 1"=30'


 DESIGNED: RSW
 DATE: 04/14
 CHECKED: BTA
 DATE: 04/14


 JURISDICTION:
 SHEET 22
 OF 50

CIVIL ENGINEERING. CIVIL RESPONSIBILITY.

NEEL-SCHAFFER

SIGNAL PHASING DIAGRAM






EXISTING SIGNAL HEAD TYPES

| PREE | MPT TABLE |
|----------|-----------------|
| DETECTOR | PHASE(S) CALLED |
| 2 | 2 + 6 |
| 4 | 4 + 8 |
| 6 | 2 + 6 |
| 8 | 4 + 8 |


| | DETECTOR ASSIGNMENTS | | | | | | | | |
|------|----------------------|----------|------|-------|----------|--|--|--|--|
| ZONE | TYPE | TYPE | ZONE | TYPE | TYPE | | | | |
| 2-1 | VIDEO | PRESENCE | 6-1 | VIDEO | PRESENCE | | | | |
| 2-2 | VIDEO | PRESENCE | 6-2 | VIDEO | PRESENCE | | | | |
| 2-3 | VIDEO | PRESENCE | 6-3 | VIDEO | PRESENCE | | | | |
| 2-4 | VIDEO | PRESENCE | 6-4 | VIDEO | PRESENCE | | | | |
| 2-5 | LOOP | PULSE | 6-5 | LOOP | PULSE | | | | |
| 4-1 | VIDEO | PRESENCE | 8-1 | VIDEO | PRESENCE | | | | |
| 4-2 | VIDEO | PRESENCE | 8-2 | VIDEO | PRESENCE | | | | |
| 4-3 | VIDEO | PRESENCE | 8-3 | VIDEO | PRESENCE | | | | |
| 4-4 | LOOP | PULSE | 8-4 | LOOP | PULSE | | | | |

1. SEE DETAIL SHEET D-03 FOR TYPICAL COUNT ZONE DETAIL.

4 - INSTALL RACK MOUNT ADVANCE DETECTION AMPLIFIER (4 @ 1-PER APPROACH).




JAMES RD/STAGE RD @ OLD AUSTIN PEAY HWY



REMOVAL NOTES: 1. REMOVE EXISTING BASE MOUNT CABINET. 2. REMOVE UNUSED DETECTOR CABLES FROM CABINET TO NEAREST PULL BOX OR

> NUMBER OF CABLES, LOOPS, ETC. X) NUMBER OF CONDUCTORS, PAIRS, ETC.



IL-06 DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.

B1 RETAIN AND MODIFY EXISTING CABINET

| B5 | INSTALL BASE MOUNTED HUB CABINET

B7 INSTALL FIBER DISTRIBUTION BOX

B9 INSTALL TRAFFIC SIGNAL PULLBOX

B15 MLGW POWER SERVICE CONNECTION

C6 | INSTALL ETHERNET CABINET SWITCH

D2 INSTALL EVP CONFIRMATION BEACON

D3 INSTALL EVP CONFIRMATION LAMP

D8 INSTALL EVP PHASE SELECTOR

D9 INSTALL VIDEO DETECTION PROCESSOR

D13 INSTALL RADAR DETECTION SYSTEM

D14 VIDEO REMOTE MANAGEMENT CARD

W1 EVP DETECTOR CABLE(S)

| W4 | VIDEO DETECTOR CABLE(S)

W5 2C DETECTOR CABLE(S)

W9 DROP CABLES (6-FIBER)

9 INSTALL 2" PVC CONDUIT

11 INSTALL 2" RGS CONDUIT

/12\ INSTALL 3" PVC CONDUIT

28 INSTALL CABLES IN EXISTING POLE

35 ATTACH CONDUIT TO BRIDGE

10 JACK AND BORE 2" CONDUIT

W7 SMFO TRUNK CABLE

| W6 | SMFO CABLE

W11 RDS CABLE

D16 INSTALL BLUETOOTH DETECTION SYSTEM

| W2 | EVP CONFIRMATION BEACON POWER CABLE(S)

| W3 | EVP CONFIRMATION LAMP POWER CABLE(S)

3 INSTALL 2" RISER INTO BOTTOM OF CABINET

 $\sqrt{6}$ Install 2" conduit entrance into existing foundation

/13\ INSTALL 3" CONDUIT ENTRANCE INTO EXISTING FOUNDATION

/25\ INSTALL CABLES IN EXISTING POLE IN EXISTING WEATHERHEAD

26 INSTALL CABLES IN EXISTING POLE IN PROPOSED WEATHERHEAD

/16\ INSTALL 3" RGS CONDUIT ON EXISTING STRUCTURE

/32\ LASH TO EXISTING MESSENGER WIRE/SPANWIRE

D12 INSTALL NEW POLE MOUNTED RDS CABINET

C2 INSTALL 8-PHASE CONTROLLER

C7 INSTALL SERIAL DEVICE SERVER

C8 INSTALL ETHERNET HUB SWITCH

D1 INSTALL EVP DETECTOR

B13 INSTALL 20' PEDESTAL POLE

B10 INSTALL FIBER OPTIC PULLBOX TYPE A

B11 INSTALL FIBER OPTIC PULLBOX TYPE B

B6 INSTALL WEATHER PROOF SPLICE ENCLOSURE

B3 INSTALL NEW BASE MOUNTED CONTROLLER CABINET

C4 REMOVE EXISTING CONTROLLER AND INSTALL NEW CONTROLLER

D5 INSTALL VIDEO DETECTION CAMERA WITH TYPE 2 MOUNT

D6 INSTALL VIDEO DETECTION CAMERA WITH TYPE 3 MOUNT

D10 INSTALL DETECTOR AMPLIFIER (4-CHANNEL) IN CABINET


B2 REMOVE EXISTING CABINET


STAGE ROAD OLD AUSTIN PEAY HWY INTERSECTION LAYOUT

DATE: N/A BOOK: N/A SCALE: 1"=30' SURVEY: N/A DRAFTED: DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14 ____ SHEET 23 OF 50

POWERS HILL DESIGN CIVIL RESPONSIBILITY.

NEEL-SCHAFFER
Solutions you can build upon





EXISTING SIGNAL HEAD TYPES


| PREEI | MPT TABLE |
|----------|-----------------|
| DETECTOR | PHASE(S) CALLED |
| 2 | 2 + 6 |
| 4 | 4 + 8 |
| 6 | 2 + 6 |
| 8 | 4 + 8 |


| | D | ETECTOR A | SSIGNM | IENTS | | |
|------|-------|-----------|--------|-------|----------|--|
| ZONE | TYPE | TYPE | ZONE | TYPE | TYPE | |
| 2-1 | VIDEO | PRESENCE | 6-1 | VIDEO | PRESENCE | |
| 2-2 | VIDEO | PRESENCE | 6-2 | VIDEO | PRESENCE | |
| 2-3 | VIDEO | PRESENCE | 6-3 | VIDEO | PRESENCE | |
| 2-4 | VIDEO | PRESENCE | 6-4 | VIDEO | PRESENCE | |
| 2-5 | LOOP | PULSE | 6-5 | LOOP | PULSE | |
| 4-1 | VIDEO | PRESENCE | 4-1 | VIDEO | PRESENCE | |
| 4-2 | VIDEO | PRESENCE | 4-2 | VIDEO | PRESENCE | |
| 4-3 | VIDEO | PRESENCE | 4-3 | VIDEO | PRESENCE | |
| 4-4 | LOOP | PULSE | 4-4 | LOOP | PULSE | |

STAGE RD @ COLEMAN RD

1. COST FOR INSTALLATION OF PROPOSED WEATHERHEAD SHALL BE ABSORBED IN

COST OF OTHER ITEMS. 2. SEE DETAIL SHEET D-03 FOR TYPICAL COUNT ZONE DETAIL.





CABINET TO NEAREST PULL BOX OR

POLE BASE.

NUMBER OF CABLES, LOOPS, ETC. X) NUMBER OF CONDUCTORS, PAIRS, ETC.

1L - 07

B1 RETAIN AND MODIFY EXISTING CABINET

| B5 | INSTALL BASE MOUNTED HUB CABINET

B7 INSTALL FIBER DISTRIBUTION BOX

B9 INSTALL TRAFFIC SIGNAL PULLBOX

B13 INSTALL 20' PEDESTAL POLE

B10 INSTALL FIBER OPTIC PULLBOX TYPE A

B11 INSTALL FIBER OPTIC PULLBOX TYPE B

B15 MLGW POWER SERVICE CONNECTION

C6 | INSTALL ETHERNET CABINET SWITCH

D2 INSTALL EVP CONFIRMATION BEACON

D3 INSTALL EVP CONFIRMATION LAMP

D8 INSTALL EVP PHASE SELECTOR

D9 INSTALL VIDEO DETECTION PROCESSOR

D13 INSTALL RADAR DETECTION SYSTEM

D14 VIDEO REMOTE MANAGEMENT CARD

W1 EVP DETECTOR CABLE(S)

| W4 | VIDEO DETECTOR CABLE(S)

W5 2C DETECTOR CABLE(S)

W9 DROP CABLES (6-FIBER)

9 INSTALL 2" PVC CONDUIT

/11\ INSTALL 2" RGS CONDUIT

/12\ INSTALL 3" PVC CONDUIT

28 INSTALL CABLES IN EXISTING POLE

35 ATTACH CONDUIT TO BRIDGE

/10\ JACK AND BORE 2" CONDUIT

W7 SMFO TRUNK CABLE

W6 SMFO CABLE

W11 RDS CABLE

D16 INSTALL BLUETOOTH DETECTION SYSTEM

| W2 | EVP CONFIRMATION BEACON POWER CABLE(S)

| W3 | EVP CONFIRMATION LAMP POWER CABLE(S)

3 INSTALL 2" RISER INTO BOTTOM OF CABINET

 $\sqrt{6}$ Install 2" conduit entrance into existing foundation

/13\ INSTALL 3" CONDUIT ENTRANCE INTO EXISTING FOUNDATION

/25\ INSTALL CABLES IN EXISTING POLE IN EXISTING WEATHERHEAD

26\ INSTALL CABLES IN EXISTING POLE IN PROPOSED WEATHERHEAD

/16\ INSTALL 3" RGS CONDUIT ON EXISTING STRUCTURE

/32\ LASH TO EXISTING MESSENGER WIRE/SPANWIRE

D12 INSTALL NEW POLE MOUNTED RDS CABINET

C2 INSTALL 8-PHASE CONTROLLER

C7 INSTALL SERIAL DEVICE SERVER

C8 INSTALL ETHERNET HUB SWITCH

D1 INSTALL EVP DETECTOR

B6 INSTALL WEATHER PROOF SPLICE ENCLOSURE

B3 INSTALL NEW BASE MOUNTED CONTROLLER CABINET

C4 REMOVE EXISTING CONTROLLER AND INSTALL NEW CONTROLLER

D5 INSTALL VIDEO DETECTION CAMERA WITH TYPE 2 MOUNT

D6 INSTALL VIDEO DETECTION CAMERA WITH TYPE 3 MOUNT


D10 INSTALL DETECTOR AMPLIFIER (4-CHANNEL) IN CABINET

B2 REMOVE EXISTING CABINET

DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN. STAGE ROAD COLEMAN RD INTERSECTION LAYOUT

DATE: N/A BOOK: N/A SCALE: 1"=30" SURVEY: N/A DRAFTED: _ DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14 JURISDICTION: _____ _____ SHEET 24 OF 50

POWERS HILL DESIGN CIVIL RESPONSIBILITY. NEEL-SCHAFFER
Solutions you can build upon




INTERRUPTION OF SERVICE TO THE SYSTEM. 2. SEE DETAIL SHEET D-03 FOR TYPICAL COUNT ZONE DETAIL.

(ATS). CONTRACTOR TO COORDINATE WITH ATS FOR ANY MODIFICATION OR

POWERS HILL DESIGN CIVIL RESPONSIBILITY. NEEL-SCHAFFER
Solutions you can build upon

STAGE ROAD COVINGTON PIKE INTERSECTION LAYOUT


SURVEY: N/A DATE: N/A BOOK: N/A
DATE: 04/14 SCALE: 1"=30" DRAFTED: DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14 JURISDICTION: ____ _____ SHEET 25 OF 50




SURVEY: N/A DATE: N/A BOOK: N/A
DRAFTED: DATE: 04/14 SCALE: 1"=20'
DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14

JURISDICTION: SHEET 26 OF 50

NEEL-SCHAFFER
Solutions you can build upon








NEEL-SCHAFFER
Solutions you can build upon


POWERS HILL DESIGN CIVIL ENGINEERING. CIVIL RESPONSIBILITY.

DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN. STAGE ROAD RADAR DETECTION SYSTEM LAYOUT

RD-02

DATE: N/A BOOK: N/A SCALE: 1"=40' SURVEY: N/A DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14






SPLICE DIAGRAM FOR INTERSECTION #8435 JACKSON AVE/AUSTIN PEAY HWY @ WALES AVE

NOTES:

1. FIBER INTERCONNECT CENTER RACKS ARE SCHEMATIC ONLY. ACTUAL EQUIPMENT FORM MAY VARY.

| COLOR CODE TIA/EIA 598-A | |
|---|--|
| (1) BLUE (7) RED (2) ORANGE (8) BLACK (3) GREEN (9) YELLOW (4) BROWN (10) VIOLET | X - FUSION SPLICE INDIVIDUAL FIBER BUFFER TUBE SLICE OR EXPRESS ENTIRE BUFFER TUBE AS NOTED |
| (5) SLATE (11) ROSE (6) WHITE (12) AQUA | —————————————————————————————————————— |





DIVISION OF PUBLIC WORKS CONGESTION MANAGEMENT PROGRAM SIGNAL SYSTEM PROJECT SET #8 SHELBY COUNTY, TN.


SD - 01

SPLICE DIAGRAM SURVEY: N/A


__DATE: <u>N/A</u> __BOOK: <u>N/A</u> __DATE: <u>04/14</u> __SCALE: <u>N.T.S.</u> DRAFTED: DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14 JURISDICTION: ____ SHEET 28 OF 50







1. FIBER INTERCONNECT CENTER RACKS ARE SCHEMATIC ONLY. ACTUAL EQUIPMENT FORM MAY VARY.



NEEL-SCHAFFER
Solutions you can build upon

DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.
AUSTIN PEAY HIGHWAY
SPLICE DIAGRAM


SD-02

SURVEY: N/A DATE: N/A BOOK: N/A

DRAFTED: DATE: 04/14 SCALE: N.T.S.

DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14

JURISDICTION: SHEET 29 OF 50



NOTES:

1. FIBER INTERCONNECT CENTER RACKS ARE SCHEMATIC ONLY. ACTUAL EQUIPMENT FORM MAY VARY.

| COLOR CODE TIA/EIA 598-A | |
|--|--|
| (1) BLUE (7) RED (2) ORANGE (8) BLACK (3) GREEN (9) YELLOW (4) BROWN (10) VIOLET (5) SLATE (11) ROSE | X - FUSION SPLICE INDIVIDUAL FIBER BUFFER TUBE SLICE OR EXPRESS ENTIRE BUFFER TUBE AS NOTED |
| (6) WHITE (12) AQUA | —————————————————————————————————————— |

SPLICE DIAGRAM FOR

INTERSECTION #8327

JACKSON AVE/AUSTIN PEAY HWY

© JAMES RD/STAGE RD


| | ALE MA | | REVISIONS | |
|--------|--|----------|--------------|------|
| \sim | The Man And And And And And And And And And An | APPROVED | DESCRIPTIONS | DATE |
|)15 | AGRICULTU 04/03/201 | | | |
| /10 | | | | |
| | OMMERCS | | | |
| | OF TENNIN | | | |


SD - 03


DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.

AUSTIN PEAY HIGHWAY @ STAGE ROAD SPLICE DIAGRAM

| POWERS HILL DESIGN CIVIL ENGINEERING. CIVIL RESPONSIBILITY. | | SPLICE DIAGRAM | |
|---|---------------|---------------------|---------------------------------|
| CIVIL ENGINEERING. CIVIL RESPONSIBILITY. | SURVEY: N/A | DATE: N/A | BOOK: N/A |
| | DRAFTED: | DATE: <u>04/14</u> | SCALE: N.T.S. |
| NEEL-SCHAFFER | DESIGNED: RSW | DATE: 04/14 CHECKED | : <u>BTA</u> DATE: <u>04/14</u> |
| Solutions you can build upon | JURISDICTION: | | SHEET 30 OF 50 |








NOTES:

1. FIBER INTERCONNECT CENTER RACKS ARE SCHEMATIC
ONLY. ACTUAL EQUIPMENT FORM MAY VARY.



NEEL-SCHAFFER
Solutions you can build upon

@ JONES RD

DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.
AUSTIN PEAY HIGHWAY
SPLICE DIAGRAM


SD-04


SURVEY: N/A DATE: N/A BOOK: N/A

DRAFTED: DATE: 04/14 SCALE: N.T.S.

DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14

JURISDICTION: SHEET 31 OF 50





SPLICE DIAGRAM FOR RADAR DETECTION SYSTEM AP-4 JACKSON AVE/AUSTIN PEAY HWY BETWEEN COLEMAN RD & RALEIGH SPRINGS MALL


ETHERNET

EDGE SWITCH

LEGEND X - FUSION SPLICE INDIVIDUAL FIBER

COLOR CODE TIA/EIA 598-A (1) BLUE (7) RED (2) ORANGE (8) BLACK BUFFER TUBE SLICE OR EXPRESS ENTIRE BUFFER TUBE AS NOTED (3) GREEN (9) YELLOW (4) BROWN (10) VIOLET (5) SLATE (11) ROSE _____ ACTIVE FIBER (6) WHITE (12) AQUA

1. FIBER INTERCONNECT CENTER RACKS ARE SCHEMATIC ONLY. ACTUAL EQUIPMENT FORM MAY VARY.



NEEL-SCHAFFER
Solutions you can build upon

JURISDICTION: __


DIVISION OF PUBLIC WORKS CONGESTION MANAGEMENT PROGRAM SIGNAL SYSTEM PROJECT SET #8 SHELBY COUNTY, TN. AUSTIN PEAY HIGHWAY


SD-05


__DATE: <u>N/A</u> __BOOK: <u>N/A</u> __DATE: <u>04/14</u> __SCALE: <u>N.T.S.</u> SURVEY: N/A DRAFTED: DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14

SHEET 32 OF 50

SPLICE DIAGRAM








1. FIBER INTERCONNECT CENTER RACKS ARE SCHEMATIC ONLY. ACTUAL EQUIPMENT FORM MAY VARY.


| | REVISIONS | | ALE |
|------|---------------|----------------|----------------------|
| DATE | DESCRIPTIONS | APPROVED | La last ence |
| | | | AGRICULTURA (03/2015 |
| | | | |
| | | | COMMERCE STATE |
| | | | OF TENNE |
| | | | -mmic |
| | POW CIVIL ENG | ERS HIL | L DESIGN |
| | CIVIL ENG | INEERING. CIVI | L RESPONSIBILITY. |


DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.
AUSTIN PEAY HIGHWAY
SPLICE DIAGRAM

SD - 06


| CIVIL ENGINEERING. CIVIL RESPONSIBILITY. | SURVEY: N/A | DATE: N/A | _ BOOK: <u>N/A</u> |
|--|-------------------|--------------------------|------------------------|
| | DRAFTED: | DATE: <u>04/14</u> | _ SCALE: <u>N.T.S.</u> |
| N_NEEL-SCHAFFER | DESIGNED: RSW DAT | E: <u>04/14</u> CHECKED: | BTA DATE: <u>04/14</u> |
| Solutions you can build upon | JURISDICTION: | | SHEET 33 OF 50 |







1. FIBER INTERCONNECT CENTER RACKS ARE SCHEMATIC ONLY. ACTUAL EQUIPMENT FORM MAY VARY.



NEEL-SCHAFFER
Solutions you can build upon

Solutions you can build upon


BETWEEN OLD AUSTIN PEAY HWY & COLEMAN RD


DIVISION OF PUBLIC WORKS CONGESTION MANAGEMENT PROGRAM SIGNAL SYSTEM PROJECT SET #8 SHELBY COUNTY, TN. SPLICE DIAGRAM


SD-07

SURVEY: N/A __DATE: <u>N/A</u> __BOOK: <u>N/A</u> __DATE: <u>04/14</u> __SCALE: <u>N.T.S.</u> DRAFTED: DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14 SHEET 34 OF 50


JURISDICTION: ____







1. FIBER INTERCONNECT CENTER RACKS ARE SCHEMATIC ONLY. ACTUAL EQUIPMENT FORM MAY VARY.




NEEL-SCHAFFER
Solutions you can build upon


Solutions you can build upon


BETWEEN COLEMAN RD & COVINGTON PIKE

SD-08DIVISION OF PUBLIC WORKS CONGESTION MANAGEMENT PROGRAM SIGNAL SYSTEM PROJECT SET #8 SHELBY COUNTY, TN. SPLICE DIAGRAM

SURVEY: N/A __DATE: <u>N/A</u> __BOOK: <u>N/A</u> __DATE: <u>04/14</u> __SCALE: <u>N.T.S.</u> DRAFTED: DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14 JURISDICTION: ____ SHEET 35 OF 50








NOTES:

- 1. FIBER INTERCONNECT CENTER RACKS ARE SCHEMATIC ONLY. ACTUAL EQUIPMENT FORM MAY VARY.
- 2. SPLICING AND CONNECTION OF EXISTING MULTI-MODE FIBER AT THIS LOCATION SHALL BE AS DIRECTED BY THE ENGINEER.

| COLOR CODE TIA/EIA 598-A | |
|---|--|
| (1) BLUE (7) RED (2) ORANGE (8) BLACK (3) GREEN (9) YELLOW (4) BROWN (10) VIOLET | X - FUSION SPLICE INDIVIDUAL FIBER BUFFER TUBE SLICE OR EXPRESS ENTIRE BUFFER TUBE AS NOTED |
| (5) SLATE (11) ROSE (6) WHITE (12) AQUA | —————————————————————————————————————— |



NEEL-SCHAFFER
Solutions you can build upon

ETHERNET CABINET SWITCH

DROP CABLE TO HUB F CABINET

SPLICE TRAY IN PROPOSED -

6-FIBER DROP CABLE TO

INTERSECTION CABINET

SPLICE ENCLOSURE #2

ORANGE

CABLE FROM JAMES RD/ STAGE RD

AND RDS S-2 36 FIBERS IN 3 BUFFER TUBES

> AND SEAL

AND SEAL

← CAP AND SEAL /-INTERSECTION #8206 CABINET

SD-09


DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.
STAGE ROAD
SPLICE DIAGRAM


SURVEY: N/A DATE: N/A BOOK: N/A

DRAFTED: DATE: 04/14 SCALE: N.T.S.


DESIGNED: RSW DATE: 04/14 CHECKED: BTA DATE: 04/14

JURISDICTION: SHEET 36 OF 50





<u>LEGEND</u>




SEWER MANHOLE

MLGW/XO MANHOLE

SOME UTILITY INFORMATION FOR THE PROJECT WORK AREA WAS NOT PROVIDED. CONTRACTOR TO VERIFY UTILITY LOCATIONS PRIOR TO CONSTRUCTION.

UTILITY LOCATIONS SHOWN ARE DEPICTIONS OF GIS DATA PROVIDED BY MLG&W AND XO COMMUNICATIONS. THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THIS INFORMATION.



(IN FEET)

1 inch = 50 ft.

| ΞD | A L B WALLES | |
|----|---|--|
| | AGRICULTO/A/03/2015 | |
| | AGRICULTURE US/AU IS | |
| | COMMERCE | |
| | No. 10269h | |
| | OMMERCE V. 10269A COMMERCE | |
| | 1////////////////////////////////////// | |


CIVIL ENGINEERING. CIVIL RESPONSIBILITY.


NEEL-SCHAFFER
Solutions you can build upon


DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM SIGNAL SYSTEM PROJECT SET #8 SHELBY COUNTY, TN. AUSTIN PEAY HIGHWAY EXISTING UTILITIES FROM 25+00 TO 50+00


U - 02


SURVEY: N/A DATE: N/A BOOK: N/A DATE: 02/14 SCALE: 1"=50' DRAFTED: APL DESIGNED: APL DATE: 02/14 CHECKED: N/A DATE: N/A JURISDICTION: __ SHEET 38 OF 50











<u>LEGEND</u>


| — Е —— | — Е —— | EXISTING ELECTRIC LINE |
|-----------------|-----------|------------------------|
| ——OHE——— | ——OHE | EXISTING HV ELECTRIC |
| W | W | EXISTING WATER LINE |
| G | G | EXISTING GAS LINE |
| — XO(A) ——— | XO(A) | XO FIBER AERIAL |
| — XO(B) ——— | XO(B) | XO FIBER BURIED |
| —— G(A)—— | — G(A)——— | ABANDONED GAS LINE |
| SS | ss | SANITARY SEWER |
| | | |


SEWER MANHOLE

MLGW/XO MANHOLE

SOME UTILITY INFORMATION FOR THE PROJECT WORK AREA WAS NOT PROVIDED. CONTRACTOR TO VERIFY UTILITY LOCATIONS PRIOR TO CONSTRUCTION.

UTILITY LOCATIONS SHOWN ARE DEPICTIONS OF GIS DATA PROVIDED BY MLG&W AND XO COMMUNICATIONS. THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THIS INFORMATION.





NEEL-SCHAFFER
Solutions you can build upon





DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8 SHELBY COUNTY, TN. AUSTIN PEAY HIGHWAY EXISTING UTILITIES


U - 07


FROM 150+00 TO 157+00 SURVEY: N/A


DATE: N/A BOOK: N/A
DATE: 02/14 SCALE: 1"=50' DRAFTED: APL DESIGNED: APL DATE: 02/14 CHECKED: N/A DATE: N/A JURISDICTION: ___ SHEET 43 OF 50














OPTION 1 (SHOWN)- REUSE EXISTING RISER (USE THIS OPTION ONLY IF THERE IS A SPARE EXISTING RISER OR IF AN EXISTING RISER CONTAINS ONLY EXISTING COMMUNICATIONS CABLE) OPTION 2 (NOT SHOWN)- INSTALL NEW CONDUIT INTO

AERIAL ROUTING

FOUNDATION AND CONNECT TO NEW RISER (SEE DETAIL THIS

SHEET)

1. THIS DETAIL IS THE APPROVED METHOD FOR ENTRY INTO A SOLID-BASE CABINET FOUNDATION THAT HAS NO SPARE CONDUITS AVAILABLE. ALL OTHER CASES MUST RECEIVE

APPROVED EQUIVALENT. THE NEMA 3R BOX SHALL BE MADE OF GALVANIZED STEEL WITH A POWDER COATED FINISH AND SHALL HAVE A CONTINUOUS HINGE THAT IS MADE OF GALVANIZED STEEL WITH A STAINLESS STEEL PIN ON THE LEFT SIDE AND CAPTIVE SCREWS ON THE RIGHT SIDE. THE NEMA 3R BOX SHALL HAVE A HASP PROVISION (OR APPROVED ALTERNATE) ON THE RIGHT SIDE FOR PADLOCKING DOOR FOR SECURING THE DOOR.

ALTERNATIVE LOCATIONS ON THE CABINET TO SECURE THE WALL-MOUNTED JUNCTION BOX MUST HAVE PRIOR APPROVAL BY THE CITY OF MEMPHIS.

4. CONDUIT STRAP IS NOT TO BE SECURED TO THE CABINET. CONDUIT STRAP MUST BE SECURED TO THE CABINET FOUNDATION.

5. DRILL HOLE INTO CABINET AND INSTALL THREADED NIPPLE. INSTALL RUBBER GASKET, FLAT METAL WASHER AND LOCKER RING ON BOTH SIDES.


6. JUNCTION BOX SHALL BE ATTACHED SECURELY TO THE CABINET WITH FOUR METAL SCREWS. MOUNTING HOLES SHALL BE INSIDE THE BOX AROUND THE FOUR CORNERS.

7. THE CONTRACTOR SHALL APPLY SEALANT BETWEEN THE EDGE OF THE JUNCTION BOX AND THE CABINET. SEALANT SHALL BE RATED FOR OUTDOOR USE, WATER-PROOF BELOW WATER LINES, UV RESISTANT AND CLEAR OR GRAY IN COLOR.

TOP VIEW (NOT TO SCALE) CONDUIT PER PLANS 1" SPARE CONDUIT REQ'D. (COST ABSORBED) REGROUT POLE BASE AFTER INSTALLATION OF CONDUITS <u>PLAN</u> DRILL & TAP AS REQUIRED EXISTING STEEL CONDULET-CHIP AWAY BASE POLE TO ALLOW CONDUIT ENTRANCE THROUGH BOTTOM OF POLE COST TO BE ABSORBED FINISHED -GRADE EXISTING CONCRETE FOUNDATION CONDUIT MUST BE, CONDUIT AS ON THE OUTSIDE/ SHOWN ON OF CONCRETE FOUNDATION PLANS PLUS ONE SPARE STUBOUT ELEVATION CONDUIT ENTRANCE TO STEEL POLE FOUNDATION EXISTING CONCRETE POLE

OR EMBEDDED STEEL POLE

CONDUIT ENTRANCE TO EXISTING



OPTION 1 (SHOWN)- REUSE EXISTING CONDUIT OPTION 2 (NOT SHOWN) - INSTALL CONDUIT ENTRANCE INTO FOUNDATION AND CONNECT TO PULL BOX (SEE DETAIL THIS SHEET)

UNDERGROUND ROUTING

NOTES:

PRIOR APPROVAL FROM THE CITY OF MEMPHIS.

2. WALL-MOUNTED JUNCTION BOX SHALL BE A NEMA 3R CONTINUOUS HINGED ENTRY BOX OR

3. THE BOX SHALL BE MOUNTED ON THE BACK SIDE OF THE CABINET NEAR THE TOP.

EXIST. WHEELCHAIR RAMP 4.5' (TYP.) 5' (TYP.) EXIST. GRASS STRIP TO REMAIN EXIST. SIDEWALK VARIES 0'-20' EXIST. CURB EXIST. ROW AND GUTTER -PROPOSED BASE MOUNTED VARIES CABINET 4" THICK SIDEWALK VARIES 4'-12' LEXIST. GRASS STRIP TO REMAIN

1. CABINET LOCATION AND LIMITS OF NEW SIDEWALK AS DIRECTED BY THE ENGINEER.

2. MAINTAIN A MINIMUM CLEAR PATH OF 48" FROM THE EDGE OF THE CABINET BASE TO THE EDGE OF SIDEWALK.

3. FINAL CABINET LOCATION SHALL BE APPROVED BY THE ENGINEER.

BACK OF CURB

TYPICAL BASE MOUNTED CABINET INSTALLATION AND SIDEWALK REPLACEMENT DETAILS

REVISIONS DESCRIPTIONS APPROVED

NEEL-SCHAFFER

POWERS HILL DESIGN IVIL ENGINEERING. CIVIL RESPONSIBILITY.

Solutions you can build upon


DIVISION OF PUBLIC WORKS CONGESTION MANAGEMENT PROGRAM SIGNAL SYSTEM PROJECT SET #8 SHELBY COUNTY, TN. MISCELLANEOUS

D - 01

SURVEY: N/A DATE: N/A _____ BOOK: <u>N/A</u> DRAFTED: DATE: <u>02/14</u> SCALE: <u>N.T.S.</u> DESIGNED: RSW DATE: 02/14 CHECKED: BTA DATE: 02/14 JURISDICTION: ____ SHEET 48 OF 50

DETAILS FOR INSTALLING NEW CONDUIT

INTO EXISTING BASE MOUNTED CABINET FOUNDATION



WEATHER HEAD LOCATION DETAIL (PLAN VIEW)

TYPICAL POLE FIELD DRILLING DETAIL

NOTE: SEE WEATHER HEAD LOCATION DETAIL FOR POSITIONING OF WEATHER HEAD(S) RELATIVE TO THE RDS UNITS.

SECONDARY RDS POLE — DRILL SECOND HOLE FOR CASE 2 WITH TWO RDS UNITS 12" MINIMUM ON SAME POLE (SEE WEATHER HEAD LOCATION DETAIL) INSTALL SECOND RDS UNIT FOR CASE 2 \longrightarrow - INSTALL RADAR DETECTOR UNIT WITH TWO RDS UNITS ON SAME POLE ACCORDING TO MANUFACTURER'S RECOMMENDATIONS DRILL CABLE ENTRANCE HOLE -(SEE TYPICAL POLE FIELD — 12" DRIP LOOP DRILLING DETAIL THIS SHEET) - INSTALL RDS CABLE (34' MINIMUM LENGTH) — INSTALL RDS AND UTILITY CABINETS FACING AWAY FROM THE TRAVELED WAY (VERIFY THAT RIGHT-OF-WAY IS AVAILABLE). IN CASE RIGHT-OF-WAY IS NOT AVAILABLE INSTALL RDS CABINET FACING THE TRAVELED WAY. SECONDARY RDS CABINET - PRIMARY RDS CABINET ___ 2" RIGID LU FORM ELBOW DRILL AND TAP (SIZE AS REQUIRED) -CLOSE NIPPLE WITH POLE MANUFACTURE'S RECOMMENDED PAINT 7' MINIMUM 7' MINIMUM HAND HOLE — TOP OF EXISTING SIDEWALK PROPOSED 2" CONDUIT TO — F.O. PULLBOX. INSTALL F.O. DROP CABLE FROM F.O. PULLBOX TO PRIMARY RDS PROPOSED CONDUIT FOR POWER CABINET. PROPOSED 2" CONDUIT TO STANDARD PULLBOX — SERVICE CONNECTION. INSTALL POWER

PRIMARY POLE

INSTALL POWER AND ETHERNET CABLES FROM SECONDARY RDS CABINET TO PRIMARY RDS CABINET (IF SECONDARY POLE AND RDS UNIT IS CALLED FOR ON PLAN SHEETS)

SECONDARY POLE NOTE: INSTALL SECONDARY RDS POLE AS NEEDED FOR PLAN SHEETS.

<u>NOTES</u>:

SERVICE CABLE FROM MLGW PULLBOX

TO PRIMARY RDS CABINET.


1. SEE PROJECT SPECIAL PROVISIONS FOR MATERIAL AND INSTALLATION REQUIREMENTS FOR RDS UNIT, PRIMARY RDS CABINET, SECONDARY RDS CABINET AND RDS CABLE.

2. SEE TDOT STANDARD DRAWING T-SG-10 FOR CONCRETE PEDESTAL POLE FOUNDATION DETAILS. ALTERNATIVELY, A STEEL SCREW-IN ANCHOR FOUNDATION CAN BE USED. SEE TDOT STANDARD DRAWING T-L-1 FOR STEEL ANCHOR FOUNDATION DETAILS.


INSTALL POWER CABLE AND ETHERNET CABLE FROM

PRIMARY CABINET TO SECONDARY CABINET

TYPICAL RADAR DETECTION SYSTEM (RDS) ON NEW 20' ALUMINUM PEDESTAL POLE




PLAN VIEW



- 1. ANCHOR HOLES FOR STEEL CONDUIT CLAMPS TO BE: •MAXIMUM DEPTH OF 1 3/4" •MAXIMUM DIAMETER OF 3/8"
- •SPACED 4' ON CENTER 2. CONCRETE WEDGE ANCHORS WITH LOCK WASHERS SHALL BE INSTALLED

BRIDGE ATTACHMENT CONDUIT CROSSING DETAIL




DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM SIGNAL SYSTEM PROJECT SET #8 SHELBY COUNTY, TN. MISCELLANEOUS

D - 02

_DATE: N/A BOOK: N/A SURVEY: N/A DRAFTED: DATE: <u>02/14</u> SCALE: <u>N.T.S.</u> DESIGNED: RSW DATE: 02/14 CHECKED: BTA DATE: 02/14 JURISDICTION: ____


SHEET 49 OF 50






VIDEO DETECTION CAMERA MOUNTING NOTES:

- WHEN AIMING CAMERA, HORIZON SHALL NOT BE VISIBLE IN THE FIELD OF VIEW.
- 2. CAMERA ENCLOSURE ASSEMBLY SHALL BE ROTATABLE AFTER INSTALLATION TO PROVIDE PROPER ALIGNMENT.
- 3. VIDEO CABLE SHALL BE BELDEN OR ENGINEER-APPROVED EQUAL.
- 4. SUNSHIELD SHALL BE EXTENDED TO THE MAXIMUM EXTENT WITHOUT BEING IN THE CAMERA FIELD OF VIEW.



VIDEO DETECTION CAMERA MOUNTING DETAILS





DIVISION OF PUBLIC WORKS
CONGESTION MANAGEMENT PROGRAM
SIGNAL SYSTEM PROJECT SET #8
SHELBY COUNTY, TN.
MISCELLANEOUS
DETAILS

SURVEY: N/A DATE: N/A BOOK: N/A

DRAFTED: DATE: 02/14 SCALE: N.T.S.

DESIGNED: RSW DATE: 02/14 CHECKED: BTA DATE: 02/14

JURISDICTION: SHEET 50 OF 50